

SURVEY & REMONUMENTATION

FEB 18 1994

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Approved By Delta County
Land Survey Remonumentation
Peer Group Under Act 345 Of
P.A. Of 1990 On Jan 20, 1994
Robert R. Schuchling
Acting Chairman

For corners in

DELTA

(County)

Located In:

Corner Code =#

1. Public Land Survey T 40 N R 22 W G-4 & E-9
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Recorded January 21, 1994

at 9:00 o'clock a.m. in Liber 7 Page 349

William C. Thuman Reg. of Deeds.
Delta County, Michigan

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims
[G-4] W1/4 COR SEC 10 E-9] NW COR OF SEC 28

I, M.P. DAVIS, in a field survey on NOVEMBER, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-4 [W1/4 COR SEC 10] WOOD POST - A. MERRYWEATHER, D.S. - 1846 (TAMERAC 18°-N8°W -55 LINKS) (SPRUCE 6°-S10°W-34 LINKS)
M.S. McNABB - 1922 - FOUND WOOD STAKE IN PLACE - REPLACED WITH IRON PIPE
M.S. McNABB - 1944 - FOUND ABOVE MENTIONED IRON PIPE (CEDAR 7°-S71°W-24') NOTE IN McNABB'S FIELD NOTES: COR IS 3.5' WEST OF DIRECT LINE BETWEEN CORNERS

E-9 [NW COR SEC 28] WOOD POST - A. MERRYWEATHER, D.S. - 1846 (BIRCH 18°-S22°E-45 LINKS) (CEDAR 9°-S65°W-16 LINKS)
JOSEPH E. GINGRASS - 1906 - ID CORNER POSITION FROM ORIGINALS - NO WIT'S NOTED

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-4 [W1/4 COR SEC 10] CORNER MONUMENT APPARENTLY DESTROYED IN CONSTRUCTION OF RELOCATED HWY U.S. 2 & 41 - RESET CORNER POSITION BY RETRACEMENT OF WEST LINE OF SEC 10 AND ESTABLISHED COR MON 3.5 WEST OF DIRECT LINE BETWEEN COR'S & AT A PROPORTIONATE DISTANCE (BASED ON McNABB'S 1922 DISTANCES) BETWEEN SEC CORNERS N & S. CORNER FALLS IN RT. WHEEL PATH OF THE RT. LANE OF THE WEST BOUND LANE OF HWY U.S. 2 & 41
ACCEPTED CORNER POSITION AS BEING A CAREFUL & FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER.

E-9 [NW COR SEC 28] CORNER MONUMENT APPARENTLY DESTROYED DURING CONSTRUCTION OF "NEW" SOUTH HILL ROAD. EXTENDED LINE EAST FROM N1/4 COR SEC 29 & THRU THE E1/16 COR & ESTABLISHED THE COR ON THIS LINE AND AT A PROPORTIONATE DISTANCE EAST OF THE E1/16
ACCEPTED THIS POSITION AS BEING A CAREFUL & FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-4 CORNER MON IS A 2" DRILL HOLE IN CONC ROAD BED OF HWY U.S. 2 & 41 @ STA 749+17.3 PER STAMPED STATIONING IN CONC ROADBED
SURVEY MONUMENT SIGN POST NWLY EDGE OF CONC ROAD BED (NO OTHER WIT'S NEAR)
N62°W N62°W
28.40' (TO FACE) 3.74'

E-9 SET A BERNTSEN ALNB30 ALUMN MONUMENT W/A CAP STAMPED TO ID THE CORNER POSITION
SURVEY MONUMENT SIGN POST (COR IS LOCATED ON THE EASTERLY SLOPE OF A DEEP FILL SECTION OF THE "NEW" SOUTH HILL ROAD-NO WIT'S
N36°E NEAR)
2.04' (TO FACE)

NOTE: BEARINGS TO REFERENCE OBJECTS ARE MAGNETIC & DISTANCES ARE TO A NAIL IN THE CENTER OF THE OBJECT UNLESS OTHERWISE NOTED

Signed by M.P. Davis Date 11/15/93

Surveyor's Michigan License No. 16926

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2								
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

