

Approved By Delta County
Land Survey Remonumentation
Peer Group Under Act 345 Of
P.A. Of 1990 On 12/30, 1997

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Robert R. Shumling RLS
acting Chairman

For corners in

DELTA

(County)

Located in:

Corner Code #

1. Public Land Survey

T 40 N R 22 W

MC G-5/6 814

T R

(005)

T 40 N R 22 W

MC G/H-5

T R

(004) 813

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

Recorded Jan 5 1998

at 9:00 o'clock AM

Liber 8 Page 292

William C. Thorne
Delta County, MI Reg. of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

[G-5/6 MC BETW SEC'S 16/15] [G/H-5 MC BETW SEC'S 10/16]

I, M.P. DAVIS, in a field survey on DECEMBER, 19 97,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-5/6 [MC BETW SEC'S 16/15] A. MERRYWEATHER, D.S. - 1846-WOOD POST (TAMARACK 09°-N38°W-40 LINKS) (CEDAR 07°-N68°W-30 LINKS)
M.S. McNABB-1918-SCRIBED STAKE IN PLACE, ID FROM FURNACE ADDITION-DROVE IRON-NO WIT'S NOTED

G/H-5 [MC BETW SEC'S 10/15] A. MERRYWEATHER, D.S. - 1846-WOOD POST- (ASH 07°-S60°W- 25 LINKS) (ELM 08°-N30°E-25 LINKS)
R.A. BROTHERTON-1915-SURVEY MAP OF C.C.I. PROPERTY SHOWS M.C. IN PLACE
M.S. McNABB-1923-SURVEY OF SUPERVISOR'S PLAT NO. 1 OF VILLAGE OF KIPLING (LIBER "B" OF PLATS, PAGE 38) ID CORNER FROM SURVEY
OF C.C.I. PROPERTY-NO DESCRIPTION OF MONUMENT GIVEN OR NEW WIT'S NOTED.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-5/6 [MC BETW SEC'S 16/15] IDENTIFIED LINE BETWEEN SECTION 16/15 FROM RECOVERY OF SURVEY MONUMENTS
FROM McNABB'S 1918 SURVEY. FOUND IN PLACE POINTED REMAINS OF A WOOD POST & A 1" IRON PIPE.
ACCEPTED EXISTING MONUMENT AS BEING THE BEST AVAILABLE EVIDENCE AS TO THE LOCATION OF THE POSITION
OF THE ORIGINAL CORNER.

G/H-5 [MC(RM)BETW SEC'S 10/15] FOUND AT THE INTERSECTION OF THE EASTERLY R/W LINE OF CLIFFS AVE. (OLD HWY. 2 & 41)
AND LINE COMMON TO SEC'S. 10/15 A 1" IRON PIPE, BEING THE P.O.B. OF THE SUPERVISOR'S PLAT NO. 1 OF
THE VILLAGE OF KIPLING, EXTENDED LINE EAST FROM THE NW COR. OF SEC 15 & ESTABLISHED THE REFERENCE
ON THIS LINE NEAR THE SHORE OF LITTLE BAY DE NOC.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-5/6 SET, OVER EXISTING IRON STAKE, A BERNTSEN A1NB30 ALUM MONUMENT.
CEDAR 12' ASH 06' SPRUCE 08' SURVEY MONUMENT SIGN POST
N88°W S64°E N34°W SOUTH
54.80' 6.24' 41.97' 1.24' (TO FACE)

G/H-5 SET A 5/8" X 18" REBAR WITH A 2" ALUM CAP STAMPED TO ID THE COR POSITION.
SE COR OF CONC BLK BLDG. CORP OF ENGINEERS SURVEY MONUMENT NW COR SEC 15
N63°W S51°W WEST
743.40' 289.54' 2563.34'

NOTE: BEARINGS TO REFERENCE OBJECTS ARE MAGNETIC & DISTANCES ARE TO A NAIL IN THE CENTER OF THE OBJECT UNLESS OTHERWISE NOTED

Signed by M.P. Davis Date 12/29/97

Surveyor's Michigan License No. 16926