

SURVEY & REMONUMENTATION

JAN 14 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Approved By Delta County
Land Survey Remonumentation
Peer Group Under Act 345 Of
P.A. Of 1990 On October 31, 1992
Robert Belandier
Chairman

For corners in

DELTA

(County)

Located in:

Corner Code #

1. Public Land Survey

T 40 N R 22 W

MC E-9/10

T R

(011)

T 40 N R 22 W

MC G-8/9

T R

(010)

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

[E-9/10 MC BETW SEC'S 29/28] [G-8/9 MC BETW SEC'S 21/22]

I, M.P. DAVIS, in a field survey on NOVEMBER, 19 97,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-9/10 MC BETW SEC'S 29/28] A. MERRYWEATHER, D.S. - 1846-WOOD POST (HEMLOCK 18"-NORTH-02 LINKS) (HEMLOCK 12"-N70°W-18 LINKS) 20'
ABOVE BAY.

NO RECORD EVIDENCE OF CORNER RECOVERY AND/OR SUBSEQUENT REMONUMENTATION

G-8/9 MC BETW SEC'S 22/21] A. MERRYWEATHER, D.S. - 1846-WOOD POST- (NORWAY PINE 12"-S68°W- 181 LINKS) (DEAD WHITE PINE 18"-S32°E-32
LINKS)

NO RECORD EVIDENCE OF CORNER RECOVERY AND/OR SUBSEQUENT REMONUMENTATION.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-9/10 [MC BETW SEC'S 29/28] IDENTIFIED LINE BETWEEN SECTION 29/28 FROM THE PLAT OF SOUTH
GLADSTONE, AS RECORDED IN LIBER "A" OF PLATS ON PAGE 15, ESTABLISHED THE CORNER POSITION
ON THIS LINE AND AT RECORD DISTANCE SOUTH OF THE NW CORNER OF SEC 28.

G-8/9 [MC BETW SEC'S 21/22] FOUND AT THE INTERSECTION OF THE SOUTH R/W LINE OF MINNEAPOLIS AVE.
AND THE LINE COMMON TO SEC'S 21/22 A CONC. PLAT MONUMENT BY PERSON OR PERSONS UNKNOWN.
THIS MONUMENT CHECKS WELL WITH THE DISTANCE TO THE PLAT CORNERS AS SHOWN ON THE PLAT OF
OF THE ORIGINAL PLAT OF GLADSTONE AS RECORDED IN LIBER "A" OF PLATS ON PAGE 12. EXTENDED
LINE SOUTH FROM THE 1/4 COR COMMON TO SEC'S 21/22 THRU THE EXISTING PLAT MONUMENT AND SET
THE MEANDER CORNER ON THIS LINE AND AT RECORD DISTANCE SOUTH OF THE 1/4 CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-9/10 SET A 5/8" X 18" REBAR W/A 2" ALUM CAP STAMPED TO ID COR POSITION.

GUARD RAIL POST GUARD RAIL POST "T" INTERS SIGN POST
S25°W N85°E S30°E
2.30' 10.80' 4.50'

NOTE: CORNER POSITION IS AT A MAJOR
CITY ROAD INTERSECTION NO OTHER
WIT'S NEAR.

G-8/9 SET A 5/8" X 18" REBAR WITH A 2" ALUM CAP STAMPED TO ID THE COR POSITION.

OAK 36" W.PINE 20" W.PINE 29"
N42°W S17°W N2°E
21.40' 49.15' 48.05'

NOTE: BEARINGS TO REFERENCE OBJECTS ARE MAGNETIC & DISTANCES ARE TO A NAIL IN THE CENTER OF THE OBJECT UNLESS OTHERWISE NOTED

Signed by M.P. Davis Date 10/30/97

Surveyor's Michigan License No. 16926

Recorded Nov 5 1997
at 9:00 o'clock AM
Lib. 8 Page 242
William C. Thorne
Treasurer

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5		4		3		2		1			
3													
4	7	8		9		10		11		12			
5													
6	18	17		16		15		14		13			
7													
8	19	20		21		22		23		24			
9													
10	30	29		28		27		26		25			
11													
12	31	32		33		34		35		36			
13													

