

# SURVEY & REMONUMENTATION

APR 27 1995

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Dickinson  
(County)

Located In:

Corner Code =#

1. Public Land Survey

T 39N R 28W

G-7 & H-7

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REGISTER OF DEEDS  
DICKINSON COUNTY  
FROM 1892 TO 1994

1994 SEP - 8 AM 8:51

RECORDED

Register of Deeds Stamp & File Number

I, Edward Kazianka, in a field survey on June 9, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-7 Wood Post Sugar 10 S50E 20 lks. W. Pine 24 N55W 07 lks.  
One inch iron rod previously recorded in County Corner Book.

H-7 Wood Post Ironwood 10 N15E 20 lks. Hemlock 12 S80W 24 lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-7 One inch iron rod previously recorded. Set a County corner in place of the rod.

H-7 Section corners  $\frac{1}{2}$  mile east and west are set. 1.2 feet north and 1.3 feet east of the mid-point between the section corners found a six inch stove-pipe filled with concrete with a  $\frac{1}{2}$  inch iron pin at it's center marked "  $\frac{1}{4}$ ". Accepted it as marking the Quarter Corner and replaced it with a County corner.

ACCEPTED BY THE DICKINSON COUNTY  
SURVEY PEER GROUP AS THE OFFICIAL  
CORNER UNDER MICHIGAN PUBLIC ACT  
345 OF 1990 AT A MEETING HELD ON

9-7-94

ROIP

COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7 2 $\frac{1}{2}$  inch Alum. cap on a 3 foot Alum. rod.

Cedar 7 N77W 9.95 feet. Cedar 5 S78W 17.95 feet. Cedar 9 N39E 38.90 feet.  
Maple 4 S15E 5.78 feet. Potten Pine stump in place for Original S.T.

H-7 2 $\frac{1}{2}$  inch Alum. cap on a 3 foot Alum. rod.

Maple 32 S66E 67.75 feet. Maple 5 S17E 10.49 feet.  
Scotch Pine 6 S80W 22.82 feet. Ironwood 4 S30E 16.47 feet.  
E of Hwy U.S. 2 North 58.2 feet.

Signed by

Edward Kazianka

Date August 10, 1994

Surveyor's Michigan License No. 14765

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1993  
REVISED JAN. 1994



Liber 2

Page 99