LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

for corners in

Dickinson	_ Located In:	Corner Code #								
(County) IORWAY TOWNSHIP										
Public Land Survey	T B									
1. Fublic Land Survey	† —— B									
	† — ;; —									
2. Property Controlling	S 14 T 41N R 29W	13								
n Section	S 14 T 41N R 29W	14								
	STR									
3. Miscellaneous	SR									
Property in Sec.	STR									
4 1 - 4 11	L LDI			Regis	ter of D	eeds S	tamp 8	<u> </u>	: Numt	er
4. Lot No, Rec 5. Private Claims	corded Plat		1 A	B (D 5	E F	G H	I	JK	L
5. Private Claims	2/13/201;	2 1 1 2	2	6	 	- -	1 3		_	
			3 _	_			<u>l</u>		Ī	
, Jeremy J. Pipp , ir	n a field survey on 2/13/2013	do hereby state	4	· 7 —				سل	_,,	
hat under requirements of P.A.		Ĺ	L Ĭ							
above were in conformance with regulations and rules therefore as required in the current manual of surve							T	\Box		
nstructions of the United States Department of the Interior, Bureau of Land Management or by a decree of					Γiົ	10	1-15	<u></u>	100	—13—
1 Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established										
'e-established, monumented, recovered, found as expressed below:					<u> </u>	1	1	op	-23	24-
,			9 -				1	十	\dashv	 -
NOTE: Not more than 2 corners, all in the same town and range, may be recorded					29 	28-	27	' ——	~26-	25-
on this certificate.				+-		+	++	\dashv	+	- -
errand werthings a			12	31— 	32_	33-	3 4	•	_35	36
			13-		<u> </u>					

4. Description of original monument and accessories and/or subsequent restoration:

- (13) Southeast One-Sixteenth corner of Section 14. Not set in original survey, no evidence of subsequent establishment.
- (14) South One-Sixteenth corner common to Sections 13 and 14. Not set in original survey, no evidence of subsequent establishment.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (13) Corner position established at the intersection of the South and East One-Sixteenth lines of Section 14.
- (14) Corner position established mid-point and on-line between the East One-Quarter corner and the Southeast corner of Section 14.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(13)	DNR monument	(14) DNR	monument
13" Poplar	N46E 3.08' (1/16S,BT)	6" B. Spruce	N17E 37.07' (1/16S,BT)
6" Spruce	S73E 29.54' (1/16S,BT)	7" B. Spruce	N59E 30.85' (1/16S,BT)
4" Balsam	S41W 9.35' (1/16S,BT)	6° B. Spruce	\$21E 11.14' (1/16S,BT)
6" Balsam	N72W 8.45' (1/16S,BT)	5" B. Spruce	N88W 6.19' (1/16S,BT)
	re blazed, scribed, and	All trees are b	lazed, scribed, and
painted. M	leasurements are to nail in	painted Offeast	ments are to nail in
side of tre	e, bearings are magnetic.	side of free, b	rements are to nail in eachings are magnetic.

Signed by

Surveyor's Michigan License No.

50447

July 22, 2013

For the Michigan Department of Natural Resources

Revised May 14, 1975 Revised Jan., 1983 Rervised Oct., 1995

OARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971