LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970	7977 NOV 29 AC 10: 31
For corners in	
Dickinson Located In: Corner Code # (County) Norway Twp.	REGISTRY 5 DEEDS DICKINGS TO ECTY ROMAGE
1. Public Land Survey T41NR 29W B-9 T R T R T R T R T R T R T R T R T R T R	
3. Miscellaneous S T R MAR 24 2000 Property in Sec. S T R	Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat 5. Private Claims	A B C D E F G H I J K L M 1 2 6 5 4 3 2 1
I, Robert F. Perkins, in a field survey on Feb. 25, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:	3 4 7 8 9 10 11 12 15 6 18 17 16 15 14 13 7 8 19 20 21 22 23 24
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.	10 30 29 28 27 26 25 11 12 31 32 33 34 35 36
A. Description of original manument and accessories and/or subsequent restoration: B-9 1 Corner 30 John Burt, D.S. 1849 Original Witnesses Sugar 16" S30°E 46 Lks. Sugar 10" NO3°W 34 Lks.	
B. Description of corner evidence found and/or method applied in restoring or reestablishing co	orner:
B-9 No Evidence of Original Corner or Accessories Found. Found D.N.R. 1" Pipe Marker with 4" Brass Cap set by Billy D. Buckler, RLS on 1-12-56 from Original Evidence. Old report No. 104	ACCEPTED BY THE DICKINSON COUNTY SURVEY PEER GROUP AS THE OFFICIAL COUNTR UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 11-23-99 COUNTY REPRESENTATIVE
the land to proper the land th	position of the corner:
C. Description of monument for corner and accessories established to perpetuate locating the	P
B-9 Accepted Pipe Marker described in "B" above. New Witnesses Y. Birch 12" N60°W(M.B.) 27.50' Nail/Tag Maple 10" S87°E(M.B.) 11.20' Nail/Tag Lynn 12" S77°W(M.B.) 18.33' Nail/Tag Maple 8" S03°W(M.B.) 25.15' Nail/Tag Placed Carsonite Marker 1.1' South.	
Signed by / Coon Date Date	Nov. 5, 1999
Surveyor's Michigan License No. 12027	~ .