

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

ir corners in

Dickinson Located In: Corner Code #
(County)
ELCH TOWNSHIP
Public Land Survey T 42N R 29W E07
Property Controlling S
Section S
Miscellaneous S
Property in Sec. S

Lot No. , Recorded Plat
Private Claims

Jeremy J. Pipp , in a field survey on 6/24/2014 do hereby state
at under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
structions of the United States Department of the Interior, Bureau of Land Management or by a decree of
Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
e rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
established, monumented, recovered, found as expressed below:

OTE: Not more than 2 corners, all in the same town and range, may be recorded
n this certificate.

Description of original monument and accessories and/or subsequent restoration:

E07) Corner common to Sections 16, 17, 20 and 21. 1849: John Burt, DS. Set sugar post
itnessed by: Sugar 16 N75E 24 lks.; Hemlock 12 S52W 13 lks. 1977: Art Enger, RLS.
et DNR monument by double proportionate measurement between corners one mile south, east
nd west and two miles north witnessed by: Sugar Maple 5 N69W 19.5'; Sugar Maple 6 S78E
0.1'; Sugar Maple 6 S69W 13.6'. 2008: Michigan DNR (Paul Bressette, PS#37270) accepted
onument and noted witnesses 10" Sugar N37E 7.95' (S16.NBT), 07" Sugar S66E 20.3' (EX.
IBT), 10" Sugar S68W 13.9' (EX. NBT), 08" Sugar N76W 19.45' (EX. NBT).

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E07) As noted in previous Michigan DNR (Paul Bressette, PS#37270) LCRC: "Found Enger's
onument and witnesses as described. All witnesses are live and standing. Monument was
ewitnessed as found, and is accepted as a careful and faithful REESTABLISHMENT of the
osition of the original corner."

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E07) DNR monument
EX 11" Maple N37E 7.95' (1/4S,NBT)
EX 7" Maple S69E 20.26' (1/4S,NBT)
EX 11" Maple S68W 13.88' (1/4S,NBT)
EX 8" Maple N74W 19.44' (1/4S,NBT)

All trees are blazed, scribed, painted,
and signed. Measurements are to nail in
side of tree, bearings are magnetic. A
Carsonite rail was set North 1.5 feet.

Signed by
Surveyor's Michigan License No.



July 15, 2014

For the Michigan Department of Natural Resources, Professional Resources Division