

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

(DICKINSON COUNTY)

FOR CORNERS OF --:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. <u>42</u> N. <u>29</u> E. <u>X</u> W.		G-6
2. PROPERTY CONTROLL- <u>16</u> ING IN SECTION <u>42</u> T. <u>42</u> N. <u>29</u> E. <u>X</u> W.		14
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ E. _____ S. _____ R. _____ W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Arthur O. Enger, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 13, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner G6 (1/4 corner between Sections 15 & 16, T42N, R29W):
Sugar post (Not found. No subsequent monuments found).
Lynn 14 N14W 60 " " " " accessories ").
" 12 S43E 31 " " " " " ").

Corner 14 (South 1/16 corner between Sections 15 & 16, T42N, R29W):

Not established in original survey nor subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner G6: Re-established on line between Sec. Cor. 40.146 ch. to N and to S.

Corner 14: Established on line between Sec. Cor. 20.073 ch. S and 1/4 cor. 20.073 ch. N.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner G6: 1" I.D. x 36" iron pipe with 3 3/4" aluminum cap.
Sugar Maple 6 N80°E (mag.) 8.1 ft. "1/4S, NBT"
Sugar Maple 8 S88°W (mag.) 33.8 ft. "1/4S, NBT"
Declination is 2°45' West

Corner 14: 1" I.D. x 36" iron pipe with 3 3/4" aluminum cap.
W. Spruce 4 S 4°E (mag.) 8.4 ft. "1/16S, BT"
W. Spruce 6 N64°W (mag.) 38.6 ft. "1/16S, BT"
Declination is 1°45' West

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE March 31, 1978

MICHIGAN REGISTERED LAND SURVEYOR

Arthur O. Enger

Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 13581

