SURVEY & REMONUMENTATION

MAR 0 3 1998

LAND CORNER RECORDATION CERTIFICATE RECORDED

Fo	r corners	in SECTION		Filing	Requirer	nent of	Act 74, Mic	h. P.	A. 1970 🏻	97 O	CT -	-9 /	M 8.	20			
D.	ickinso	On (County)	_ Locat				rner Code #						5	-0			
\mathbf{F}	elch Tv									n -							
4	Dublic L	and Survey	7	/ 2 N	R <u>28W</u>		F-11		'	REGIS	TEN INSO	1 10 f	'EEDS	j			
١.	Fubile 5	and Survey			R		P=13		RI	IN MC	HÜĞ		EEDS JNTY	וחו			
			T	-	R			_							•		
			T		R			_									
2.		Controlling	s T s T		R	. —		_									
3.	in Section Miscella		s t					_									
•		in Section	S T						Regi	ster o	f De	eds S	tamp	& File	Num	ber	
		_						,	L								
4,	Lot No.	, Rec Daims	orded Plat_							A	В	СР	E F	д н	1 1	к	
Э.	rivate	латть								2	-6-		↓ _↓_	3-	į	4	
										3	+-1		╂	11	-}}	_}-	
										4	╌┦╼╌┨		 ∳	10-		-	
		<u>erkins</u> , in								5	+		┼-├-	++	++	+	
		tify that under require 2 above were in conf								6	·1 <mark>8 </mark>	17 -	16-	15-	14	+	
mar	nual of su	irvey instructions o	f the United	States	Departmer	nt of the	Interior, Bure	au of	Land	7	11		 	++	+ +	\top	
		or by a decree of a (in conformance wit								8	19	20 	 2 1~	22-	23	-	
		ourt of Law; establis	hed, re-estal	olished, ı	monumented	d, re-mon	umented, recov	vered,	found	-1	30-	29	28-	27-	26		
	expressed		U ! sk				. 1-			11			28-	Τű			
NO		more than 4 come nis certificate.	rs, all in the	same 1	own and ra	ange, ma	ly de recorded	α		12	31-		-33-	34-	35		
_			_	_	_					13			<u></u> -				
A.	=	tion of original mo				d/or sub	-										
	F-11	North & Corr Post by John			33		F-	13	South 1/2 Post by								
		Original Bea							Original					540			
		Y.Pine 20"	S5°W	14 Lk					Hemlock					Lks			
		Y.Pine 18"	N35°E	43 Lk	s.				Hemlock	17"	N	17°W	11	Lks	•		
B.	Descript	escription of corner evidence found and/or method applied in 1-11 No evidence of Original Corner or Accessories Found. Found 1 1 iron pipe set by Unknown Surveyor, buried in 1 of Dirt Road. Adjacent Metes and Bounds Parcels tied to this Corner. Corner accepted by Adjoining Property Owners as 1 Corner.					F	estoring or reestablishing corner: F-13 No evidence of Original Corner or Accessories Found. Found 1½" Iron Pipe projecting approx. 1 Foot out of Ground. Also 4 existing Witness Trees adjacent to Pipe. ACCEPTED BY THE DICKINSON COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 10-7-97 RGPP									
_			_				_						TATIVE				
C.	Descript	ion of monument	for corner a	and acc	essories e	stablish	ed to perpetu	iate k	ocating the	posit	ion o	f the	corner	7			
	F-11	Accepted Exi	F-1	13	Accepted	l ab	ove	Four	nd Pi	ipe a	ıs						
		Best Availab	le Evid	ence o	of 1 Cor	cner			Best Ren		_		dence	of			
		Location. Placed 21" S	tamped 1). C. 1	Remon (Corner			Corner I New Bear								
		Inside of Ex			icaion.	Joiner			0ak 10"				3.)	4.1	3 '		
		New Witnesse	s	-					W.Pine 1	.8 ¹¹	N55	5°E	(м.в.	.) 4	2.82	2 *	
			N83°1						Oak 311	S50	6°W	(M. I	3.)	25.0			
		REd Pine 16	" N32°			.57' .16 '		1111111	OF MICH	NI.	2 ¶ W	(M.l	5.)	15.3	4'		
		S.E. Corner		-	-			e,	,	W.	<u>.</u>						
		S51°W (M.B.)	119.20)†		•	*		ROBERT '	*							
Sign	ed by	Room	10	E	de			ate r	F. Hautuule en	- X	≣ ≣199	3 7					
Surv		ROBERT F. PERKT		7			100	TO MA	тагтен үс	. :	=		FESSIONAL	L SURVEY	IRS. JAN	— 28. 197	

Reber 2 Rage 298