

STATE OF MICHIGAN  
DEPARTMENT  
OF  
NATURAL RESOURCES  
  
LAND CORNER RECORD


Dickinson COUNTY  
T 43 N R 29 W

DESCRIPTION OF CORNER Section Corner 25, 26, 35 and 36

CORNER MONUMENT 1" I. D. x 36" iron pipe with 4" aluminum cap

DATE MONUMENT PLACED AND WITNESSED July 29, 1970

WITNESSES TO CORNER..... W. Spruce 12 N78°E (mag.) 21.7 ft. "S25, NBT"



W. Birch 8 S14½°E (mag.) 58.7 ft. "S36, NBT"

AND

CIRCLE CORNER REGISTERED

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR RESTORED.

Corner re-established by double proportionate measurement between original section corners 80.264 ch. east and 79.564 ch. west and a 1/4 section corner 40.08 ch. north and a stream crossing 6.21 ch. south. Record distance between SW cor. of Sec. 36 and 1/4 cor. bet. Sec. 25 & 26 is 120.00 ch., measured distance is 119.43 ch. (difference is 0.57 ch.), but distance between stream and 1/4 cor. bet. Sec. 25 & 26 is only .09 ch. longer than record, so stream was used for N & S proportion, rather than the SW corner of Sec. 36.

SURVEYOR'S SEAL

DISTRIBUTION:

SIGNED

*Arthur O. Enger*  
REGISTERED LAND SURVEYOR  
Arthur O. Enger

DATE January 24, 1972

County Courthouse  
Area Forester (Regions I & II)  
District or Region Surveyor  
Forestry Div., Lansing

R 4047  
Rev. 10/68