

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

DICKINSON COUNTY

| FOR CORNERS OF-- | LOCATED IN-- | CORNER CODE NUMBER |
|---|--|--------------------|
| 1. PUBLIC LAND SURVEY_____ | T. 43 N. X R. 29 X W. | C6, B7 |
| 2. PROPERTY CONTROLL- ING IN SECTION 30 | , T. 43 N. X R. 29 X W. | 7 |
| 3. MISCELLANEOUS PROPERTY IN SECTION _____ | , T. _____ N. _____ R. _____ E. _____ W. _____ | |
| 4. LOT NO. _____ | , RECORDED PLAT _____ | |
| 5. PRIVATE CLAIMS _____ | | |

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on See Below, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on_____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:
Corner 7: Not set on original survey nor subsequently apparently.

Corner C6: Original monument and accessories not found.

Corner B7: Original monument and accessories not found.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 7: Established 5-20-81 midway and on line between section corner north and $\frac{1}{4}$ corner south.

Corner C6: Restored 5-13-81 midway and on line between section corners north and south.

Corner B7: Restored 5-13-81 by proportion between section corners east and west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 7: Set 1" I.D.x32" iron pipe with 4" alum. cap.

8" Maple N20E 1.8 ft. 1/16S,BT

10" Maple S19W 23.7 ft. 1/16S,BT

5" Spruce S68E 13.7 ft. 1/16S,BT

Corner C6: Set 1" I.D.x32" iron pipe with 4" alum. cap.

8" Sugar S79E 38.4 ft. $\frac{1}{4}$ S,NBT

12" Sugar S48W 37.9 ft. $\frac{1}{4}$ S,NBT

10" Sugar N57W 34.6 ft. $\frac{1}{4}$ S,NBT

Corner B7: Set 1" I.D.x32" iron pipe with 4" alum. cap.

28" Basswood S57E 22.2 ft. $\frac{1}{4}$ S,NBT

9" Balsam N33E 11.8 ft. $\frac{1}{4}$ S,NBT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett

Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

