

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

DICKINSON COUNTY

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 43 N. 29 W.	C8, C10
2. PROPERTY CONTROLLING IN SECTION 7	T. 43 N. 29 W.	10
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO.	RECORDED PLAT	
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on See Below, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 10: Not set on original survey nor subsequently apparently.
Corner C8: Found white pine stump matching size, bearing and distance.
Corner C10: Original monument and accessories not found.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 10: Established 5-27-81 on line and proportionate distance between corners north and south.
Corner C8: Restored 5-27-81 from White Pine stump probable original bearing tree. Fits good with other corners in area.
Corner C10: Restored 5-20-81 midway and on line between section corners north and south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 10: Set 1" I.D.x32" iron pipe with 4" alum. cap.
5" Spruce S51E 26.0 ft. 1/16S,BT
8" Spruce S82W 38.6 ft. 1/16S,BT
7" Spruce N52E 16.0 ft. 1/16S,BT
Corner C8: Set 1" I.D.x32" iron pipe with 4" alum. cap.
8" Sugar S43W 13.3 ft. 1/8S,NBT
8" Sugar N88E 9.8 ft. 1/8S,NBT
9" Sugar N47W 6.8 ft. 1/8S,NBT
9" squared Basswood S83W 4 ft.
Corner C10: Set 1" I.D.x32" iron pipe with 4" alum. cap.
12" Cedar N47W 14.5 ft. 1/8S,NBT
10" Cedar S23W 19.4 ft. 1/8S,NBT
12" Cedar N42E 25.3 ft. 1/8S,NBT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____


(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett
Department of Natural Resources

DATE 10-22-83



SURVEYOR'S MICHIGAN REGISTRATION NO. 19006