

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in  
Dickinson

Located In:

Corner Code FF

1. Public Land Survey	T	43N	R	29W	FS
	T	43N	R	29W	NO
	T		R		
	T		R		
2. Property Controlling	S	15	T	43N	R
in Section	S		T		R
3. Miscellaneous	S		T		R
Property in Sec.	S		T		R

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

9 June 02, 1994

NO June 02, 1994

I, Stephen J. Szyszkoski, in a field survey on FS May 04, 1994, 19\_\_\_\_\_, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(FS) Quarter corner common to Sections 9-10. Original corner established in 1848 by Harvey Mellon as follows: Set cedar post. Cedar 8 N19W 12, Cedar 10 S84E 12. Found no subsequent record.  
 (NO) Center of Section 15. Corner not established in the original survey. Found no subsequent record.  
 (9-Sec. 15) East 1/16 Corner Section 15. Corner not established in the original survey. Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(FS) Original post and accessories not recovered. Several old cedar stumps are in the corner area but none will match the record. The area has been severely burned over long ago. Found no acceptable evidence of the position of the original corner on the ground. Reestablished the corner on a straight line between Section corners 2634.50' East and West, being the proportionate position. At the position for the corner, I placed a 1" I.D.x32" iron pipe capped with a 4" dia. cast aluminum MONR tablet, appropriately stamped.  
 (NO) Found no evidence of prior monumentation at the corner position. Established the corner at the intersection of straight lines connecting opposite 1/4 corners, all monumented. At the position for the corner, I placed a 1" I.D.x32" iron pipe capped with a 4" dia. cast aluminum MONR tablet, appropriately stamped. The corner falls in a grass airstrip, 35' wide, bearing N77E-S77W, and approximately 8' Southeastly from the north edge.  
 (9-Sec.15) Found no evidence of prior monumentation at the corner position. Established the corner on a straight line between Center of Section 1327.90' West and Quarter corner 1327.90' East. At the position for the corner, I placed a 1" I.D.x32" iron pipe capped with a 4" dia. cast aluminum MONR tablet, appropriately stamped.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(FS) Set 1" pipe with 4" MONR cap. Blazed and scribed the following new bearing trees:  
 8" Spruce N41W 19.6' 1/4S NBT  
 13" Spruce S13E 30.8' 1/4S NBT  
 6" Spruce S45E 24.9' 1/4S NBT  
 7" Spruce N43E 41.6' 1/4S NBT  
 Set a 4" squared cedar post adjacent. Bearings are magnetic.

(NO) Set 1" pipe with 4" MONR cap, set flush. Set measuring nails with MONR ref. tags in the following trees:  
 7" Aspen S80W 51.4' not marked  
 6" Aspen S49E 87.5' not marked  
 Set a 1" I.D.x36" iron witness pipe, projecting 2" N49W 40.9'  
 An unmarked 3" spruce - the only one in the area-bears S75E 130.1'. Bearings are magnetic.

(9) Set 1" pipe with 4" MONR cap. Blazed and scribed the following bearing trees:  
 9" Cedar S84E 54.9' 1/16S BT  
 15" Tamarack S70E 27.1' 1/16S BT  
 3" Balsam S34W 7.1' 1/16S BT  
 10" Tamarack N15E 41.1' 1/16S BT  
 Set a 4" squared cedar post adjacent. Bearings are magnetic.

Signed by

Stephen J. Szyszkoski

Date

7-14-94

Surveyor's Michigan License No.

33986

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1977

