## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

for corners in

Dickinson	La cada d I	0 0 1 "		
	_ Located In:	Corner Code #		
VEST BRANCH TOWNSHIP  I. Public Land Survey	ТR	<del></del>		
2. Property Controlling n Section	T R S 18 T 44N R 27W S 18 T 44N R 27W S T R	11 12		
3. Miscellaneous Property in Sec.	S T R S T R		Register of Deeds Stamp & File Number	
1. Lot No. , Red 5. Private Claims	corded Plat		A B C D E F G H I J K L	
	9/19/201	3AD	2 - 6 - 5 - 4 - 3 - 2 - 1 -	
, Jeremy J. Pipp, i			e 3	
hat under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2				
above were in conformance with regulations and rules therefore as required in the current manual of survey 5				
nstructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6 to Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with 7				
he rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established			o, 8 19 20 21 22 23 24	
e-established, monumented, recovered, found as expressed below:			9   1   1   1   1   1   1   1   1   1	
NOTE: Not more than 2 corron this certificate.	ners, all in the same town and range	e, may be recorded	10 30 29 28 27 26 25 11 12 31 32 33 34 35 36	
			131	

- A. Description of original monument and accessories and/or subsequent restoration:
- (11) Southwest One-Sixteenth corner of Section 18. Not set in original survey, no evidence of subsequent establishment.
- (12) Center-South One-Sixteenth corner of Section 18. Not set in original survey, no evidence of subsequent establishment.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (11) Corner position established at the intersection of the South and West One-Sixteenth lines of Section 18.
- (12) Corner position established mid-point and on-line between the Center One-Quarter corner and the South One-Quarter corner of Section 18.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11)	DNR monument	(12) DNR monument
6" Maple	N18E 14.77' (1/16S,BT)	6" Maple N39E 5.56' (1/16S,BT)
9" Maple	S63E 17.39' (1/16S,BT)	5" Maple S30E 9.31' (1/16S,BT)
12" Maple	\$12W 40.12' (1/16\$,BT)	5" Maple \$51W 12.17' (1/16S,BT)
10" Maple	N26W 18.30' (1/16S,BT)	6" Maple N22W 14.96' (1/16S,BT)
All trees a	re blazed, scribed, and	All trees eresplazed, scribed, and
painted. Measurements are to nail in		painted. The asovements are to nail in
side of tre	e, bearings are magnetic.	paints OF Masonements are to nail in

signed by \_\_\_\_\_

Surveyor's Michigan License No.

0447 PROFESSIONAL

October 1, 2013

ATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

Department of Angural Possures Private Possures Dide

20286

Revised May 14, 1975 Revised Jan., 1983 Rervised Oct., 1995