

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Dickinson	Located In:	Corner Code #
(County)		
WEST BRANCH TOWNSHIP		
1. Public Land Survey	T _____ R _____	
	T _____ R _____	
	T _____ R _____	
2. Property Controlling in Section	S 17 T 44N R 27W	12
	S 21 T 44N R 27W	15
	S _____ T _____ R _____	
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	
	S _____ T _____ R _____	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Jeremy J. Pipp, in a field survey on 9/23/2013AD 9/25/2013AD do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(12) Center-South One-Sixteenth corner of Section 17. Not set in original survey, no evidence of subsequent establishment.

(15) West One-Sixteenth corner common to Sections 21 and 28. Not set in original survey, no evidence of subsequent establishment.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(12) Corner position established mid-point and on-line between the Center One-Quarter corner and the South One-Quarter corner of Section 17.

(15) Corner position established mid-point and on-line between the South One-Quarter corner and the Southwest corner of Section 21.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(12) DNR monument  
11" Cedar N02E 38.91' (1/16S,BT)  
10" Tamarack N52E 35.11' (1/16S,BT)  
12" Tamarack N81E 50.41' (1/16S,BT)  
12" Tamarack S10E 84.45' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

(15) DNR monument  
9" Cedar N81E 38.58' (1/16S,BT)  
14" Cedar S36E 21.95' (1/16S,BT)  
10" Spruce N88W 32.08' (1/16S,BT)  
7" Spruce N37W 11.40' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

Signed by Jeremy J. Pipp  
Surveyor's Michigan License No. 50447

For the Michigan Department of Natural Resources, Forest Resources Division



Date October 1, 2013

20294

20302

Revised May 14, 1975  
Revised Jan., 1983  
Revised Oct., 1995