

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Dickinson	Located In:	Corner Code #
(County)		
Sagola Township		
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 19 T 44N R 29W	7
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Jeremy J. Pipp, in a field survey on 2/16/2012AD do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(07) North One-Sixteenth corner common to Sections 19 and 20. 1975 Michigan DNR (Aurther Enger PS#13581) set 1" I.D. x 24" pipe with 3 1/2" aluminum cap witnessed by Red Maple 6 S63E 30.5 "1/16thS, BT" & Red Maple 4 NORTH 33.7 "1/16thS, BT".

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(07) Accepted found MDNR Monument and existing Witness (North). Position is accepted as a careful and faithful PERPETUATION of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(07) DNR monument
EX. 6" Maple N03E 33.78' (1/16S,BT)
13" Red Maple N86E 46.37' (1/16S,NBT)
4" Red Maple S42W 42.00' (1/16S,NBT)
6" White Birch N43W 20.45' (1/16S,NBT)
All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.



Signed by Jeremy J. Pipp
Surveyor's Michigan License No. 50447

Date July 16, 2012

For the Michigan Department of Natural Resources, Office of Land and Facilities