MICHGAN STATEBOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1976 REVISED JAN., 1983 REVISED OCT., 1998

JAN 1 1 2001

SECTION	Filing Requi	ER RECORDATION CERT irement of Act 74, Mich. P	IFICAÐÐ JUN 19 A .a. 1970	M 10: 10
For corners in		FIELD TOWNSHIP R OF SECTION 13	LINDA M. TWI	TCHELL
EATON	Located In:	Corner Code #	necter and the	116 5 115
(County)			EATON COUNT	firition.
1. Public Land Survey	T <u>1N</u> R <u>4W</u> T R T R	L-6		***** <b>*</b>
Property Controlling in Section	TR STR		LIBER	4 PAGE 122
3. Miscellaneous Property in Sec.	S T R S T R	<u> </u>	Register of D	Deeds Stamp & File Number
4. Lot No, Re	corded Plat		A B C D	P P C U T T V T W
5. Private Claims				E F G H I J K L M
state that under requirements lines 1 and 2 above were in current manual of survey instru Management or by a decree of and 5 above were in conforma	, in a field survey on of P.A. 74, Michigan P.A. of 18 conformance with regulations are titions of the United States Departs a Court of Law and for that the lince with the rules of the Michigablished, re-established, monume	970, the corner points mentione nd rules therefore as required in rtment of the Interior, Bureau of I corner points mentioned in lines gan Board of Land Surveyors or	d in the 4 7 8 8 .end 5 3, 4 by a 6 18 17	16 15 14 13 21 22 23 24
NOTE: Not more than 2 com on this certificate.	ers, all in the same town and ran	nge, may be recorded	10 30 29	28 27 26 25
1. VOL. 1, PAGE 12, EATO BUT DID NOT DESCRIBE OF 2. VOL. 2, PAGES 118-11: 1880, IDENTIFIED THE COP PROVIDE WITNESSES OR L CORNERS.	INAL GOVERNMENT SURVEY ON COUNTY SURVEYOR J.H. R WITNESS IT ON HIS MAP. 9, EATON COUNTY SURVEY RNER MARKER AS A STONE INEAL DISTANCES TO ANY (	GIBBONS NOTED THIS COR JAN., 1868 OR, W.H. BAILEY , FEB. 11-1 AND STAKE BUT DID NOT CARDINAL GOVERNMENT	3,	
AFTER TRAVERSING EN INTERSECTION OF THE 1/4 LINES IN ANY OF THE CAR 345, P.S. 18994 AT THE IF REDUNDANT BY THIS SUR CENTER OF SECTION AND OF SECTION. POINT BEING POSITION FOR FUTURE SU SHORT TIME DURING SPRI DURING THE SUMMER. W	vidence found and/or method VTIRE SECTION 13 AND ESTA LINES. POSITION IS IN A CU- IDINAL DIRECTIONS. SET A 3 NTERSECTION OF THE 1/4 LI- IVEYOR. ALSO SET A 3/4" X THE 1/4 CORNER COMMON IS FEET SOUTH OF THE SOU IRVEYS SINCE THE ACTUAL ING AND IN THE FALL., OTHE ITNESSED AS: SET N&T #18994 .09 FEET.	ABLISHING PROPER 1/4 CORI JLTIVATED FIELD WITH ABSI 3/4" X 24" FORM PIN AND 2- NES, 2 FEET BELOW THE GR 24" FORM PIN WITH A EATI TO SECTIONS 13 AND 12 A JTHERLY EDGE OF ANGLING CENTER OF SECTION MARKI ERWISE FROZEN UNDER BAR 3994, S/SIDE, 8" BOX ELDER	NERS, INVERSED TO TO DLUTELY NO FENCE, C -1/4" EATON COUNTY OUND SURFACE WHIC ON COUNTY DISK ON I T A POINT 769.18 FEE THUMA ROAD AND ER WOULD ONLY BE A REN GROUND IN THE V AZ. 90°, 13.34 FEET	DCCUPATION OR TREE DISK STAMPED P.A. H WAS DEEMED LINE BETWEEN THE ET NORTH OF THE CENTER MORE PRACTICAL CCESSIBLE DURING A WINTER AND IN CROPS ; SET N&T #18994, E/SIDE
SET 3/4" X 24" IRON B SET NAIL & TAG #18994 SET NAIL & TAG #18994 SET NAIL & TAG #18994 SOUTH, 330 FEET MORE OF NORTH, 769.18 FEET TO NORTH, 2637.01 FEET	TO NORTH 1/4 CORNER TO SOUTH 1/4 CORNER O EAST 1/4 CORNER	DISK IN MIDDLE OF CULTIVA CKORY, AZ. 98°32', 267.62 CHERRY, AZ. 174°35', 331 RY, AZ. 214°34', 384.42 FEE FENCE ON THE EDGE OF A	TED AND ACTIVE FIEL FEET .53 FEET ET VET LAND TO THE SOI EDGE OF THUMA ROAI	.D 2 FEET BELOW SURFACE. JTH.
Surveyor's Michigan Licens	a No 1899	4		

P.A. 345 EATON COUNTY
PEER APPROVED 5/16/2000 ILL