

SURVEY & REMONUMENTATION

JAN 11 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 ROXAND TWP.

For corners in

Eaton Located In: Corner Code #
(County)

1. Public Land Survey T 4N R 5W D-11
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

I, RON HELSEL, in a field survey on JUNE 19, 20 00 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
ORIGINAL MONUMENT: POST SET BY ORANGE RISDON, U.S. DEPUTY SURVEYOR, MAR., 1827. SET 40.0 CHAINS AT AVG. DISTANCE. SUGAR 12", N39°W, 29 LINKS; SUGAR 14", S43°E, 33 LINKS.
DID NOT FIND ANY FURTHER RECORDS PUBLIC OR PRIVATE CONCERNING THIS CORNER. EATON CO. ROAD GRID MAP HAD GOVERNMENT BEARING TREES FOR THEIR WITNESSES.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
EXCAVATED A 6' BY 6' HOLE IN THE INTERSECTION OF STRANGE HWY. AND LOUCKS ROAD, DOWN 1.5' TO 2' FOUND A ROUND BOWLING BALL SIZED STONE WITH RAILROAD SPIKES ON THE NORTH AND EAST SIDES. I HAVE FOUND SEVERAL STONES AND RAILROAD SPIKES THROUGH OUT EATON COUNTY, NONE OF WHICH WERE OF PUBLIC RECORD BUT HAVE BEEN ACCEPTED AS MARKERS FOR THE CORNERS. DID NOT FIND ANY OTHER EVIDENCE OF A PREVIOUS CORNER. ACCEPTED THE POSITION OF THE STONE AS FAITHFUL PERPETUATION OF THE CORNER AND SET A STANDARD 3/4" BY 24" FORM PIN WITH THE EATON COUNTY P.A. 345 DISK. CORNER IN THE PHYSICAL CENTER LINES OF STRANGE HWY. AND LOUCKS ROAD.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
FORM PIN AND DISK STAMPED P.A. 345, P.S. 18994 A THE CENTER LINES OF THE ROADS, 6" BELOW GRAVEL SURFACE.
SET NAIL & TAG NO. 18994, WEST/SIDE 16" WALNUT, NORTH. AZ. 347°, 73.82 FEET
SET NAIL & TAG NO. 18994, NW/SIDE 8" WOOD POST, NORTH AZ. 39°, 45.85 FEET
SOUTHWEST CORNER OF HOUSE FOUNDATION NORTH AZ. 72°, 150.79 FEET
SET NAIL & TAG NO. 18994, SE/SIDE POWER POLE, NORTH AZ., 231°, 75.25 FEET
MEASURED EAST, 2642.97 FEET TO E-11
MEASURED SOUTH, 5284.84 FEET TO D-13
MEASURED WEST, 2638.16 FEET C-11
MEASUED SOUTH, 2642.12 FEET TO D-12

00 AUG 14 AM 11:00

LINDA M. TWITCHELL
REGISTER OF DEEDS
EATON COUNTY, MICH.

LIBER 4 PAGE 138

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

Signed by Ron Helsel
Surveyor's Michigan License No. 18994

Date Aug. 2, 2000

