

SURVEY & REMONUMENTATION

FILED

JAN 11 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE JUN 19 AM 10:09
Filing Requirement of Act 74, Mich. P.A. 1970
ROXAND

For corners in

EATON

(County)

Located In:

Corner Code #

LINDA M. TWITCHELL
REGISTER OF DEEDS
EATON COUNTY, MICH.

1. Public Land Survey

T 4N R 5W

E-11

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

LIBER

4 PAGE 120

Register of Deeds Stamp & File Number

I, RON HELSEL, in a field survey on MAY 3, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
ORIGINAL MONUMENT: POST SET BY ORANGE RISDON, U.S. DEPUTY SURVEYOR, MAR., 1827. 40.00 CHAINS NORTH FROM 1/4 CORNER COMMON TO SECTIONS 32 & 33. ELM 10", S81°W, 20 LINKS; ASH 9", N80°E, 62 LINKS. MARGIN NOTE OF EATON CO. ROAD COMM. COPY OF GLO NOTES, UNDATED, CALLED FOR "LARGE STAKE-WAGON AXLE, THIMBLE OVER IT- S. SIDE OF CAUSEWAY- NOTHING FOR WITNESSES" ADDITIONAL WITNESS BY H.A.W. (CO. SURVEYOR WILLIAMS), DATED 1922 WITNESSED AS: IRON ANC. POST N41°W-43.6'; & ANC. POST S53°W-38.6'.


- 1) VOL. 1, PAGE 45, NO DATE, CO. SURVEYOR W.D. SOUTHWORTH, NO WITNESSES OR DESCRIPTION OF CORNER.
- 2) VOL. 1, PAGE 47, JUNE, 1867, CO. SURVEY W.D. SOUTHWORTH, NO WITNESSES OR DESCRIPTION OF CORNER.
- 3) VOL. 1, PAGE 204, OCT. 27, 1874, CO. SURVEYOR OSCAR CHURCH CALLED FOR A STAKE AS ESTABLISHED, NO WITNESSES.
- 4) VOL. 3, PAGE 14, CO. SURVEYOR, W. SOUTHWORTH, OCT., 1891 CALLED FOR A LARGE STAKE, WAGON AXLE AND THIMBLE AS DESCRIBED IN THE MARGIN NOTE ABOVE AND WITNESSED AS THE SAME.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND A 2" SOLID STEEL ANCHOR POST NORTHWEST AND 25 FEET MORE OR LESS WEST OF AN OLD ROAD BED TO THE SOUTH. FOUND A CIRCLE OF STONES 25 FEET WEST OF OLD ROAD BED, SOUTHWEST OF THE PI OF STRANGE HWY. AND THE OLD ROAD BED TO THE SOUTH. I BELIEVE THESE ARE THE TWO WITNESSES NOTED IN THE MARGIN OF THE ECRC GLO NOTES BY HARVEY WILLIAMS IN 1922. INTERSECTED THE DISTANCES AND EXCAVATED DOWN 4 FEET INTO THE BLUE CLAY BELOW THE ROAD FOUND A PIECE OF DRAG LINE CABLE AND NUMEROUS OTHER METAL OBJECTS BUT NOTHING THAT INDICATED A PREVIOUS CORNER. AREA HAS HAD SERIOUS EXCAVATION IN THE PAST FOR COUNTY DRAIN PIPES AND ROAD C.M.P.'S UNDER STRANGE HWY. AND ADJOINING DITCHES. DEEMED THE CORNER AS OBLITERATED AND ACCEPTED THE CENTER OF THE CIRCLE OF STONES AND THE 2" STEEL ANCHOR POST AS WILLIAMS ORIGINAL WITNESSES. SET A 3/4" X 24' FORM PIN AND EATON CO. REMON. DISK STAMPED P.A. 345, P.S. 18994. CORNER 2.5 FEET SOUTH OF CENTERLINE STRANGE HWY. & 3 FEET EAST OF CENTERLINE OF THE OLD ROAD BED TO THE SOUTH. MEASURED 2644.11 TO E-12 AND 5280.48 FEET TO A FOUND AND UNRECORDED 1/2" IRON BAR AT C-11.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3/4" FORM PIN AND STANDARD EATON COUNTY REMON. DISK STAMPED P.A. 345 SET NAIL AND TAG NO. 18994 EAST/SIDE UTILITY POLE, AZ. 234°, 38.19 FEET CENTERLINE 2" SOLID STEEL ANCHOR POST, AZ. 318°, 43.68 FEET SET NAIL AND TAG NO. 18994 WEST/SIDE POWER POLE, AZ. 32°, 64.25 FEET CUT "V" INTO SOUTH END OF 24" C.M.P. UNDER ROAD, AZ. 136°, 19.41 FEET CUT "V" INTO EAST END OF 12" C.M.P. UNDER ABANDONED ROAD, AZ. 165°, 22.87 FEET



Signed by

Ron Helsel

Date

MAY 31, 2000

Surveyor's Michigan License No.

18994

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1976

REVISED JAN., 1983

REVISED OCT., 1998

P.A. 345 EATON COUNTY
PEER APPROVED 5/10/2000 RL