

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Emmet
(County)

Located In

Corner Code #

1. Public Land Survey T R
T R
2. Property Controlling in Section S 36 T 37N R 5W 3
S 36 T 37N R 5W 4
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on March 16, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

3- N 1/16 Cor., common to Sec.'s 35 & 36, T37N, R5W 4- NW 1/16 Cor., Section 36, T37N, R5W
None None

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

3- N 1/16 Cor. common to Sec.'s 35 & 36, T37N, R5W 4- NW 1/16 Cor., Section 36, T37N, R5W
Set stamped 2" alum. cap on 5/8"x34" rebar per standard BLM procedure. Found no other evidence to dispute the location for the corner. Set stamped 2" alum. cap on 5/8"x34" rebar per standard BLM procedure. Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3- N 1/16 Cor. common to Sec.'s 35 & 36, T37N, R5W 4- NW 1/16 Cor., Section 36, T37N, R5W
Stamped 2" Aluminum cap on 5/8"x34" rebar Witnesses: N38°E 19.55' to set N&T on NW side 12" S.Maple S78°E 18.29' to set N&T on S side 8" S.Maple S15°W 16.90' to set N&T on SE side 12" S.Maple N19°W 12.39' to set N&T on W side 11" S.Maple West 24' to C/L N-S 2-track Set Blue Carsonite Post w/loc. tag 1' North Stamped 2" Aluminum cap on 5/8"x34" rebar Witnesses: N05°E 16.94' to set N&T on W side 10" S.Maple N75°E 19.74' to set N&T on S side 12" Twin S.Maple S03°E 7.40' to set N&T on W side 6" S.Maple S67°W 22.60' to set N&T on S side 14" S.Maple West 15' to N-S wire fence remains. Set Blue Carsonite Post w/loc. tag 1' North

Carl T. Kiiskila

Surveyor's Michigan License No.: 33981

7-15-09

