

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Emmet Located In Emmet Corner Code # Emmet
(County)

1. Public Land Survey T 37N R 5W K-12
T 37N R 5W M-12
2. Property Controlling in Section S T R
S T R
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 12, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-12 1/4 Corner, common to sections 35 & 36, T37N, R5W M-12 1/4 Corner, common to section 31, T37N, R4W & section 36, T37N, R5W.

1840 - GLO - John Mullett - Set Qr. Sect. Post.

Beech 10" S10°E 25 links

Beech 15" N21°W 18 links

2005 - ALTA ACSM Land Title Survey - Richard E.

Oelke, P.S.#33983 - Set 5/8" CIR, by single prop.

2006 - L.C.R.C. - L.4, p.80 - Richard E. Oelke, P.S.#33983

- Fd. no evidence of GLO corner or occupation.

Set 5/8" CIR per single prop. measurement. N35°E

8.45' 10" Maple, S25°E 24.02' 5" Maple, S46°W

18.53' 8" Beech, N40°W 12.94' 12" Twin Maple

1840 - GLO - John Mullett - Set Qr. Sect. Post.

Hemlock 7" N12°W 7 links

Sugar 14" S32°W 13 links

2002 - Field notes - Thomas D. Swenor P.S.#37282 -

Fd. and accepted 3/4" Pipe.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

K-12 1/4 Corner, common to sections 35 & 36, T37N, R5W M-12 1/4 Corner, common to section 31, T37N, R4W & section 36, T37N, R5W.

Fd. 5/8" CIR#33983 per Oelke survey. Accepted fd. iron as the best available evidence of the position of the original corner.

Fd. 3/4"x1.3' Iron Pipe with down barbed wire fence Running N-S through corner. N-S powerline east 27' from corner. Accepted found pipe as the best available evidence of the position of the original corner. Replaced fd. pipe w/standard MDNR mon.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-12 1/4 Corner, common to sections 35 & 36, T37N, R5W M-12 1/4 Corner, common to section 31, T37N, R4W & section 36, T37N, R5W.

Fd. 5/8" CIR#33983

Witnesses:

N34°E 8.46' to Fd. N&T on NW side 12" S.Maple

S46°E 23.98' to Fd. N&T on W side 7" S.Maple

S23°W 18.48' to Fd. N&T on S. side 10" Beech

N38°W 12.96' to Fd. N&T on E. side 13"&16"

Twin S.Maples

Set Blue Carsonite Post 1' North

Stamped 4" alum. MDNR cap on 1"x3' galv. pipe.

Witnesses:

N17°E 9.96' to set N&T on W side 6" S.Maple

S01°W 12.95' to set N&T on W side 17" Elm

S45°W 23.98' to set N&T on NW side 11" Beech

N76°W 7.02' to set N&T on S side 6"&4" Twin

S.Maple

Set Blue Carsonite Post 1' North

Signed by:

Carl T. Kiiskila

Date:

7-15-09

Surveyor's Michigan License No.:

33981

