LAND CORNER RECORDATION CERTIFICATE

trans (man)

	DEGLUDEMENT	ΩE.	ACT	74	MICH	PA 1970
FILING	REQUIREMENT	OF	ACI	/4,	MICH.	P.A.1970

	LOCATED IN -:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	т. <u>37</u> ^{N.} , к. <u>5</u>	₩. K-11;	
2. PROPERTY CONTROLL- 2	5 ,T 37 N. R. 5	10; 5	
3. MISCELLANEOUS PROPERTY IN SECTION	,T N. S., R	E.	
4. LOT NO, RE	ECORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in re-established, monumented, and rules therefore as require Bureau of Land Management and 5 above were, in a field si	n lines 1 and 2 above were, is re-monumented, recovered of in the current manual of sor by a decree of a court of arvey on	by certify that under requirements of a field survey onOCTOBER or restored as expressed below and urvey instructions of the United Slaw, Furthermore, that the corne, 19, found, recovered, rest the Michigan State Board of Regist	5, 19.82, established in conformance with regulations states Department of the Interior r points mentioned in lines 3, tored, established or re-established
	5		
	5/8" ROD W/CAP 24" CHERRY N74 12" CHERRY N9°		
K-11 - SET CORNER IN SURVEY IN SEC	lence found and or method a N LINE WITH FENCE CTION 26. IN LIN	applied in restoring or re-establishin SOUTH AT LOCATION E E ROADS NORTH AND EA	STABLISHED IN 1962 ST.
K-11 - SET CORNER IN SURVEY IN SEC 10 - SET BY STANDA 5 - SET BY STANDA	dence found and/or method and LINE WITH FENCE CTION 26. IN LIN ARD SURVEY PROCED ARD SURVEY PROCED for corner and accessories ending 20.3*	SOUTH AT LOCATION E	STABLISHED IN 1962 ST. OF SECTIONS. SION OF SECTIONS. e position of the corner:
K-11 - SET CORNER IN SURVEY IN SEC 10 - SET BY STANDA 5 - SET BY STANDA C. Description of monument K-11 DNR MONUMENT (BURIED 4" R. MAPLE S45°W	dence found and/or method and LINE WITH FENCE CTION 26. IN LIN ARD SURVEY PROCED ARD SURVEY PROCED for corner and accessories ending 20.3*	SOUTH AT LOCATION E E ROADS NORTH AND EA URE FOR SUBDIVISION URE FOR THE SUBIDIVI stablished to perpetuate locating the 10 3/8" X 10" ROD 6" R. MAPLE N61 7" R. MAPLE S67	STABLISHED IN 1962 ST. OF SECTIONS. SION OF SECTIONS. e position of the corner:
K-11 - SET CORNER IN SURVEY IN SEC 10 - SET BY STANDA 5 - SET BY STANDA C. Description of monument K-11 DNR MONUMENT (BURIEF 4" R. MAPLE \$45°W 7" W. BIRCH \$18°E SURVEYOR'S MICHIGAN FOR STATE AND UNITED	conce found and or method and LINE WITH FENCE TION 26. IN LIN ARD SURVEY PROCED TO CORNER and accessories end	SOUTH AT LOCATION E E ROADS NORTH AND EA URE FOR SUBDIVISION URE FOR THE SUBIDIVI stablished to perpetuate locating the 10 3/8" X 10" ROD 6" R. MAPLE N61 7" R. MAPLE S67 5" CEDAR POST W/ OF CORNER DATE/O-	STABLISHED IN 1962 ST. OF SECTIONS. SION OF SECTIONS. e position of the corner: e position of the corner: CE 50.6' CE 79.1' LOC TAG 45' EAST CENTROL LAND SURVEYOR NO. 10068
K-11 - SET CORNER IN SURVEY IN SEC 10 - SET BY STANDA 5 - SET BY STANDA C. Description of monument K-11 DNR MONUMENT (BURIED 4" R. MAPLE S45°W 7" W. BIRCH S18°E SURVEYOR'S MICHIGAN FOR STATE AND UNITED SIGNED BY	conce found and or method and LINE WITH FENCE TION 26. IN LIN ARD SURVEY PROCED TO CORNER and accessories encountry accessories encountry and accessories encountry accessories encountry accessories encountry and accessories encountry accessories encountry accessories encountry and accessories encountry ac	SOUTH AT LOCATION E E ROADS NORTH AND EA URE FOR SUBDIVISION URE FOR THE SUBIDIVI stablished to perpetuate locating the 10 3/8" X 10" ROD 6" R. MAPLE N61 7" R. MAPLE S67 5" CEDAR POST W/ OF CORNER	STABLISHED IN 1962 ST. OF SECTIONS. SION OF SECTIONS. e position of the corner: e position of the corner: CE 50.6' CE 79.1' LOC TAG 45' EAST COSTLING LAND SUBSELVOR NO. 10068