

1995 RE-MONUMENTATION PROGRAM

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

GENESEE

(County)

Located In:

Corner Code =/

1. Public Land Survey

T 6N R 6E

L-5

2. Property Controlling
In Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

20123

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	1	2	3	4	5	6	7	8	9	10	11	12	13
3	14	15	16	17	18	19	20	21	22	23	24	25	26
4	27	28	29	30	31	32	33	34	35	36	37	38	39
5	40	41	42	43	44	45	46	47	48	49	50	51	52
6	53	54	55	56	57	58	59	60	61	62	63	64	65
7	66	67	68	69	70	71	72	73	74	75	76	77	78
8	79	80	81	82	83	84	85	86	87	88	89	90	91
9	92	93	94	95	96	97	98	99	100	101	102	103	104
10	105	106	107	108	109	110	111	112	113	114	115	116	117
11	118	119	120	121	122	123	124	125	126	127	128	129	130
12	131	132	133	134	135	136	137	138	139	140	141	142	143
13	144	145	146	147	148	149	150	151	152	153	154	155	156

I, RICHARD H. KRAFT, In a field survey on, DECEMBER, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1823 - GLO - HARVEY PARKE, DEPUTY SURVEYOR - SET CORNER - NO ACCESSORIES
1955 - JOHN MAKIE - RECORDED PLAT - S 88°49' E, 664 FT.
1995 - R. FRANK - FOUND RE-ROD IN MONUMENT BOX - 4 ACCESSORIES

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1995 GENESEE COUNTY RE-MONUMENTATION PROGRAM

1955 - FOUND 1 ACCESSORY
1995 - FOUND 2 ACCESSORIES

Ratified by Peer Group in
accordance with P.A. 345, 1990

Co. Rep. Carl Kahn

Date 12-27-95

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET STANDARD GENESEE COUNTY MONUMENT IN MONUMENT BOX

FOUND NAIL & TAG - 14" WALNUT - S 45° E, 58.45 FT.
FOUND NAIL & TAG - 8" WALNUT - S 5° E, 34.4 FT.
FOUND NAIL & TAG - 8" TREE - N 15° W, 41.3 FT.
FOUND GOULD TAG - POWER POLE - NORTH - 60.0 FT.

SURVEY &
REMONUMENTATION

MAY 31 2000

SECTION

Signed by

Richard H. Kraft

Date

12-29-95

Surveyor's Michigan License No.

10064