

SURVEY &
REMONUMENTATION

AUG 6 8 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Gogebic County }

For corners in

Gogebic

(County)

Located in:

Corner Code #

1. Public Land Survey Sec. 32 T 44N R 39W C-12-13
T R
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Section S T R

4. Lot No. , Recorded Plat
5. Private Claims

Closing Section Corner common to S-31 and S-32 T44N R39W on Michigan State Line

I, John R. Garske, in a field survey on November 11, 19 96,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current
manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and
5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found
as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- Original corner established by Wells Burt, U.S. Deputy Surveyor on August 27, 1851 set wood Post from which bears a spruce pine 12" - N 22°W - 26 links and a yellow pine 8" - N18° E - 30 links.
- Gary Pisoni, RLS found a large metal hub (axle shaft) with 1 1/2" dia. hole in center located at closing corner position between sections 31 and 32 on the Mich- Wis. state boundary line, corner was set by an unknown land surveyor or Pisoni set a 5/8" dia. by 24" rebar in center of hub with a plastic survey cap on rebar and from which he established the following witnesses: J. Pine 16" - S77° E - 38.83 feet, iron pipe 3/4" - N01°-17'E - 10.37 feet, white birch (double) 22" - S49°W - 31.38feet, J. Pine 22" - N 41°W - 43.30 feet.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- Found a 5/8" x 24" rebar with a plastic survey cap on the rebar, set by Gary Pisoni, RLS. in a axle shaft. Found Pisoni's bearing trees.
- I replaced Gary pisoni's rebar with a 3/4" rebar with a standard bernsten aluminum cap, which was set just below grade and in quick-crete.
- This location has been used by various surveys and accepted as the closing corner between sections 31 and 32.
- This corner represents the closing corner between sections 31 and 32 on the Mich-Wis. state boundary line located in T44N, R39W.

(Record Research on File)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- Replaced the Plastic "Pisoni" cap inside the axle shaft with a 3/4" rebar with a 3 1/4" aluminum cap (inside the axle shaft) stamped: County Remonumentation; Established the following: T44N, R39W S.31, S.32 MI, WI, 1996, RLS 28410, witnesses and reference objects:
- Reference monument (set) - 2 1/2" aluminum pipe with 3 1/4" aluminum cap stamped N50°W- 42.18 feet - Powerpole with sign - N50°W- 0.94 feet.
- (existing) 18" J. Pine - N 78°E - 38.76 feet
- (existing) 20" J. Pine - N 38°W - 43.30 feet
- (existing) White birch clump - S49°W -31.41 feet

Signed by John R. Garske

Date 5/12/97

Surveyor's Michigan License No. 28410

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN, 1983

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5		4		3		2				
3												
4	7	8		9		10		11		12		
5												
6	18	17		16		15		14		13		
7												
8	19	20		21		22		23		24		
9												
10	30	29		28		27		26		25		
11												
12	31	32		33		34		35		36		
13												



X-Z-5 127