

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }  
Gogebic County } ss.

Received for record the  
11<sup>th</sup> day of AUGUST  
A. D. 1993 at 9:15 o'clock  
A m., and recorded in  
Liber 4 of CORNERS  
on page 245

*Betty Harris, Deputy*  
Register of Deeds

Register of Deeds Stamp & File Number

For corners in  
Gogebic

Located In: Corner Code #/

1. Public Land Survey

T 46 N R 40W

1, B-1W

T R

002

T R

T R

2. Property Controlling  
in Section

S T 46N R 40W

ONT. COUNTY

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

58.78 CHS. WEST

Gary L. Pisoni March 29 19 91

I, Gary L. Pisoni, in a field survey on March 29, 1991, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by John Burt, U.S. Deputy Surveyor on July 9, 1847.  
Original corner: 10" Hemlock as corner tree  
No original bearing tree set.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner evidence found. Corner restored by single proportionate measurement methods on line between the Northwest corner of Section 6, T45N, R40W and the East meander corner between Sections 32 and 5.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position, I set a standard 2" diameter by 30" long split base aluminum pipe monument with a 3" cast aluminum cap, stamped to read: T46N, R40W, M.C., S-31, S-6, T45N, 1991, R.L.S. 27457; from which I established the following new blazed and scribed bearing trees: (all measurements taken to a nail in side of tree) 12' from waters edge.

Hemlock	7"	N 09° W	22.12 feet
Hemlock	6"	N 27° E	16.86 feet
Hemlock	11"	S 19° E	11.74 feet
Steel sign post		East	0.85 feet

PEER GROUP APPROVED  
*Richard P. D... 1/20/94*  
COUNTY REPRESENTATIVE



Signed by *Gary L. Pisoni*

Date August 6<sup>th</sup>, 1993

Surveyor's Michigan License No. 27457

U.S.F.S. #A-2,3 (East side of West Bay)