

JAN 22 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic _____
(County)

Located In:

Corner Code ~~74~~

- | | | |
|---------------------------------------|----------------------------------|------------|
| 1. Public Land Survey | T <u>45N</u> R <u>41W.</u> | <u>I-6</u> |
| | T _____ R _____ | _____ |
| | T _____ R _____ | _____ |
| | T _____ R _____ | _____ |
| 2. Property Controlling
in Section | S _____ T _____ R _____ | _____ |
| | S _____ T _____ R _____ | _____ |
| 3. Miscellaneous
Property in Sec. | S <u>i</u> _____ T _____ R _____ | _____ |
| | S _____ T _____ R _____ | _____ |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

$\frac{1}{4}$ Corner 14 & 15; T.45 N., R.41 W.

I, Richard L. Drahn in a field survey on December 13, , 19 97 , do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by A. Merryweather on 6/12/1852. Original B.T.s--- 9" Cedar S.20 W. 3 links (1.98') --- 4" Balsam N.75 E. 10 links (6.60') --- 1901 R.R. print provides; 58' East to, and 120' south to R.R. Fred Serena, Forester, on 5/3/60 recovered the corner marked by a post. John P. Smallwood RLS for MSHD on 6/7/61 referenced three B.T.s to the corner. Richard L. Drahn (21564) on 10/26/89 monumented this corner at the site of the wood post in accord to the old R.R. ties and Smallwoods B.T.s. He set a 2" X 30" aluminum pipe with a 3½" stamped alum. cap and the following:

- | | | | |
|--|-----------------|---------|--------|
| 7" | Twin Red Maple | S.65 E. | 22.76' |
| 9" | Tamarack | N.62 W. | 32.66' |
| B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: | | | |
| 11" | Tamarack | N.59 E. | 13.38' |
| 6' | Steel sign rail | N.51 E. | 2.2' |

Corner recorded in Gogebic County Liber 3, Page 296 on 1/23/90.

Corner research on file with Gogebic County records.

Recovered the monument as described and the bearing trees as follows:

- | | | | |
|-----|-----------------|---------|--------|
| 9" | Twin Red Maple | S.48 E. | 22.76' |
| 10" | Tamarack | N.63 W. | 32.65' |
| 12" | Tamarack | N.59 E. | 13.39' |
| 6' | Steel sign rail | N.50 E. | 2.17' |

No evidence of the original B.T.s remain.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

- 8" Red Maple S.70 W. 22.28'

PEER GROUP APPROVAL

Richard L. Wadon 12/19/97
COUNTY REPRESENTATION

Signed by Richard L. Drakun Date December 15, 1997

Surveyor's Michigan License No. 21564

USFS L-17

291

Register's Office } ss.
Gogebic County }

Received for record the
22ND day of DECEMBER

A. D. 1997 at 11:00 o'clock

 A. m., and recorded in

Lib. 6 of CORNER

on page 291

Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number[illegible]