

SURVEY & REMONUMENTATION

NOV 12 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Gogebic County }

Received for record the
9TH day of OCTOBER
A. D. 1997 at 10:50 o'clock
A. m., and recorded in
Liber 6 of CORNERS
on page 223
Ramonna Collins Deputy
Register of Deeds

Register of Deeds Stamp & File Number

For corners in

Gogebic
(County)

Located In:

Corner Code ##

- | | | |
|---------------------------------------|-------------|--------|
| 1. Public Land Survey | T 45N R 46W | DE 1-2 |
| | T R | |
| | T R | 011 |
| | T R | |
| 2. Property Controlling
in Section | S T R | |
| | S T R | |
| 3. Miscellaneous
Property in Sec. | S T R | |
| | S T R | |

4. Lot No. , Recorded Plat
5. Private Claims

Mile Corner No. 2, Mich. --- Wisc. State Line

I, Richard L. Drahn in a field survey on September 24, 19 97, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by William Burt in 1847. Original B.T. ---- Sugar 10"
N. 75½ W. 685 links --- " no other bearing trees" ---

Corner re-established by Earl G. Harrington by proportionate methods in 1928 on a dependent re-survey of the State Line. He set a standard brass capped concrete monument two new B.T.s --- Y. Birch 8" S.48-40 W. 21.8' --- Y. Birch 8" N.37-36 E. 31.35' ---

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Recovered the concrete monument as described in Harringtons notes and the following 1928 B.T.s : 12-14" downed Yellow Birch with portions of the blaze still intact at N.37½ E. 31.4' and a live 18" Yellow Birch with blaze and scribing grown over at S.48½ W. 21.96' (new nail in side of B.T.)

Research form on file with Gogebic County records.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the above described concrete monument I established the following:

- | | | | |
|-----|-----------------|---------|--------|
| 13" | Sugar Maple | N.03 E. | 16.47' |
| 10" | Sugar Maple | S.65 E. | 17.94' |
| 6' | Steel sign rail | N.05 E. | 2.99' |

PEER GROUP APPROVED
Richard L. Drahn 10/8/97
COUNTY REPRESENTATIVE



Signed by Richard L. Drahn

Date September 29, 1997

Surveyor's Michigan License No. 21564

USFS AB 7-8