

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Gogebic County

FOR CORNERS OF--

LOCATED IN--

CORNER CODE NUMBER

1. PUBLIC LAND SURVEY T. 46 N. 8. R. 42 W.

D-3

2. PROPERTY CONTROLLING IN SECTION T. S. R. E. W.

3. MISCELLANEOUS PROPERTY IN SECTION T. S. R. E. W.

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

Quarter Corner Sections 5 & 8; T.46N., R.42W.

I, Richard L. Drahn do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on June 17 1991, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by A. Merryweather, U.S. Deputy Surveyor, on August 19, 1851.
Original bearing trees:

B.Ash	7"	S.51°E.	20 links	(13.20 feet)
Birch	10"	N.39°W.	30 links	(19.80 feet)

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

No evidence found of original survey. No evidence of subsequent corner restoration found. Corner position re-established on line between and equal distance from the monumented northeast and northwest section corners of Section 8; T.46N., R.42W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 3/4" outside diameter by 7 foot long aluminum rod monument with a 3" cast aluminum cap, stamped to read: T.46N., R.42W.; 1/4; S-5, S-8; 1991; R.L.S. 21564. From which I have established the following new blazed and scribed bearing trees:

12"	Hemlock	N.60°W.	15.57 feet
6"	Yellow Birch	N.62°E.	16.22 feet
6"	Black Ash	S.52°W.	9.13 feet
6'	Steel rail	S.17°E.	1.93 feet

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Richard L. Drahn DATE January 12, 1994

E-7

SURVEYOR'S MICHIGAN REGISTRATION NO. 21564

Register's Office }
Gogebic County } ss.

Received for record the
14th day of JANUARY
A. D. 1994 at 10:10 o'clock
A m., and recorded in
Liber 4 of CORNERS
on page 375
Betty Saine Deputy
Register of Deeds
REGISTER OF DEEDS STAMP AND
FILING NUMBER

PEER GROUP

Approved

Richard L. Drahn 1/20/94

Betty Saine Deputy
Register of Deeds