

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Gogebic County }

For corners in

Gogebic (County)	Located In:	Corner Code ##
1. Public Land Survey	T 46N R 43W	E-11
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Received for record the
12TH day of MAY
A. D. 1999 at 10:55 o'clock
A m., and recorded in
Liber 7 of CORNERS
on page 106
Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Section Corner, 28, 29, 32 & 33; T.46 N., R.43 W.

I, Richard L. Drahn in a field survey on April 27, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on 9/16/1851. Original B.T.s --- Lynn 16" S.36 W. 4 links (2.64') --- Cedar 10" N.39 E. 7 links (4.62') ---
Corner position re-established by Richard L. Drahn, RLS 21564, on 7/21/92 by double proportionate methods. He set a 2½" X 30" aluminum pipe with a 3¼" stamped aluminum cap and the following new B.T.s: --- 14" Sugar Maple N.28 E. 23.20' --- 11" Sugar Maple S.07 W. 7.05' --- 10" Sugar Maple S.51 W. 10.18' --- 6' metal sign rail N.52 W. 1.66' ---

Corner recorded in Gogebic County Liber 4, Page 171 on 10/8/92.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Recovered the monument as described and the bearing trees as follows:
15" Sugar Maple N.26 E. 23.18'
12" Sugar Maple S.06 E. 7.04'
11" Sugar Maple S.49 W. 10.17'
6' Steel sign rail N.52 W. 1.64'

No evidence of the original corner or bearing trees remain.

Corner research on file with Gogebic County records.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

5" Sugar Maple N.68 W. 14.99'

Richard L. Drahn
Surveyor
5/11/99



Signed by Richard L. Drahn Date April 19, 1999

Surveyor's Michigan License No. 21564