

SURVEY & REMONUMENTATION

DEC 15 1998

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in **SECTION**
Gogebic

Register's Office
Gogebic County ss.

Received for record the
25th day of NOVEMBER
A. D. 1998 at 10:00 o'clock
A m., and recorded in
Liber 7 of CORNERS
on page 93
Ramona Collins, Deputy
Register of Deeds

	Located In:	Corner Code #
	Section <u>2</u> <u>46N</u> <u>47W</u> <u>K-3</u>	
1. Public Land Survey	T <u> </u> R <u> </u>	
	T <u> </u> R <u> </u>	
	T <u> </u> R <u> </u>	
	T <u> </u> R <u> </u>	
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	
	S <u> </u> T <u> </u> R <u> </u>	
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	
	S <u> </u> T <u> </u> R <u> </u>	

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

1/4 corner 1 & 11,12, T46N, R47W

I, John R. Garske in a field survey on 11-19, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original Township subdivision by William Ives, D.S. in Sept. 1848.
set post at corner from which:
W. Birch 16" N45°E 2 links
Hemlock 16" S18°W 26 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I established the ~~xxx~~ corner at the intersection of Kinnunen and VanBirkirk Roads. This position fits well with fence lines at "40" line crossings north and south of the corner.
N00°-03' 08E - 2640.03 feet to 1/4 corner 35 & 36.
S00° - 19' 05" W - 2635.21 feet to 1/2 corner 1 & 2.

(Research on file)

DEED GROUP AFFIDAVIT
Richard L. Dean 11/24/98
COUNTY REGISTER

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the section corner at the road centerline intersection I set 3 1/4" dia stamped brass cap on a 5/8" x 12" iron rod from which I established: Reference Monument - 2 1/2" x 30" aluminum pipe monument with a 3 1/4" dia. stamped aluminum cap S 53°W 40.00 feet
steel sign rail 1.00 feet
8" maple N47°W 85.70 feet
power pole N50°E 43.67 feet
10" b. spruce S435°E 89.75 feet

Signed by John R. Garske
Surveyor's Michigan License No. 28410

Date 11/24/98

