

1993

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Gogebic County }

Received for record the
16th day of DECEMBER
A. D. 1993 at 2:25 o'clock
P m., and recorded in
Liber 4 of CORNERS
on page 301
Betty Loomis, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

For corners in

Gogebic
(County)

Located In:

Corner Code ##

1. Public Land Survey Section 5 T 47N R 46W D-3
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

One-quarter corner common to S-5 & 8, T47N, R46W

November 30 93

I, John R. Garske, in a field survey on , 19 ,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Survey by Austin Burt, U.S.D.S., June 18, 1851. Set post from which a 6" sugar bears N5°W,
22 links and a 16" lynn bears S14°E, 25 links. No original evidence found.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3" brass capped pipe stamped: 1/4 cor.; Section 5 and Section 8; Land mark set by County
Surveyor. Corner has been used in the recorded Plat of Powderville Hamlet and several other
surveys of record and Gogebic County Road Commission plans of Powderhorn Road.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Three inch diameter brass capped pipe stamped: 1/4 cor.; S-5; S-8; Land mark set by County
Surveyor: Established the following bearing trees and reference objects:

6" maple - S72°E - 7.92 feet
4" cherry - S10°E - 12.50 feet (slope dist.)
4" oak - N10°W - 12.25 feet
JRG Concrete monument with iron rod due north 33.00 feet
Steel sign post - SW'ly - 1.83 feet

Signed by John R. Garske
Surveyor's Michigan License No. 28410

Date 12/9/93

