SURVEY & REMONUMENTATION

SEP 0 8 1998

	AND ARREST H	- A
SE.		ON

Register's Office Gogebic County ss.

	SECTIO	N Filing Requir	ement of Act 74, Mich.	PA 1970	Receive	ed for record th	4
For corners	s in	rang nequa	ement of Act 74, Mich.	-		ay of MAY	-
Gogeb	i C (County)	Located In:	Corner Code ##		_	and recorded in	_
1. Public	Land Survey	T <u>47N</u> R <u>44</u> W T <u>B</u>	<u>I-1</u>	4	iber 6 page 361	Of CORNER	5
	ty Controlling	s T <u>48N R 44W</u>		•		Register of Deed	
in Sect 3. Miscell Properl		S T R S T R S T R		Register of Deeds Stamp & File Number			
		Recorded Plat		 	A B C D E	ғ б. н д Ј к	(L
5. Private	Claims	<u>,</u>		2	6 5	4 3 2	\Box
Section	on Corner	2, 3, 34 & 35; T.4	17-48 N., R.44 W	. 3 4	7 8	9 10 11	
do hereby ce in lines 1 ar current man Managemen above were i	ertify that under red nd 2 above were in ual of survey instri it or by a decree of in conformance wi aw; established, i	Anin a field survey on Apriquirements of P.A. 74, Michigan P.A n conformance with regulations are uctions of the United States Depart a Court of Law and/or that the corner the rules of the Michigan Board re-established, monumented, re-	of 1970, the corner points men nd rules therefore as required rtment of the Interior, Bureau o er points mentioned in lines 3.4 of Land Surveyors or by a Deci	in the 6 in the 7 tand 5 8 ee of a 9 ind as 10	18 17 20	21 22 23 28 27 26	2
	ot more than 4 c this certificate.	corners, all in the same town a	nd range, may be recorded	j 11 12 13	-31 - 32	33 34 35	31
A. Descri	ption of original	monument and accessories an	d/or subsequent restoration	-			
10" N	.61 E. 26	shed by Austin Burt links (17.16') E. 15 links (9.90'	- Sugar 8" N.34 N	W. 53 lin	ks (34.98	31)	')
remain stampe	ns of the ed brass c 5" Sug 8" Sug	l by Donald D. Lapp fouroriginal B.T.s cap and the following S.72 far Maple S.75 far Maple S.16 for Maple S.16	s. He set a 2" 1 Ing new bearing to W. 12.6' 7 E. 21.2'	K 60" iro trees:	n pipe wi	lecayed .th a 3"	
Corne	r recorded	l in Gogebic County	in USFS Liber,	Page Z-1	7 on 3/31	./69.	
		on file with Goge					
1: 1: Remain	7" Sug 1" Sug 5" Sug ns of the	nonument as describ gar Maple S.70 gar Maple N.61 gar Maple S.18 original B.T.s are	<pre>0 W. 12.67' 1 E. 21.12' 3 W. 26.73' 2 still evident.</pre>	(new nail)		
C. Descrip	ption of monume	ent for corner and accessories	established to perpetuate	locating the po	sition of the co	orner:	
New be	earing obi	ects referenced:			اجتند	ASSESSMENT OF THE PARTY OF THE	

Steel sign rail N.13 W. 3.03'

x 7' Cedar sign post bears S.40 E. 2.32'

L. DRAHN LAND SURVEYOR No. 21564

May 3, 1998

Surveyor's Michigan License No. 21564