

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

	<u>Gogebic</u> (County)	Located In:	Corner Code #
1. Public Land Survey		<u>T.48N R.45W.</u>	<u>K-7</u>
		T. R.	
		T. R.	
		T. R.	
2. Property Controlling in Section	S. T. R.		
	S. T. R.		
3. Miscellaneous Property in Sec.	S. T. R.		
	S. T. R.		

Register's Office } ss.
Gogebic County }

Received for record the
22ND day of SEPTEMBER
A. D. 1999 at 1:00 o'clock
P m., and recorded in
Liber 7 of CORNERS
on page 248
Ramona Collins, Deputy
Register of Deeds
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Section Corner 13, 14, 23 & 24 T.48 N., R.45 W.

I, Richard L. Drahn, in a field survey on September 17, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
Original corner established by Austin Burt on 9/17/1848. Original bearing trees:
Y. Birch 10" S.34° E. 27 links (17.82')
Sugar 10" N.15° W. 48 links (31.68')

C. Supercynski on 4/9/35 recovered a 24" Birch scribed "45 N 48 W 13" laying 27 ft. NE of a Spruce stake. He placed a location poster on the NW side of a 10" Hemlock from which the Spruce stake lay N.28°W. 17 feet.

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I restored the corner position at record bearing and distance from the remains of the two original bearing trees. The first is a large series of root holes with Yellow Birch bark. The second one is now an almost completely decayed Sugar Maple stump.

A 32" Yellow Birch witness tree, still scribed with a "W & N" bears N.60° E. 25.32' from the original corner location.

The 1935 location poster was recovered on the NW side of a 17" Hemlock bearing S.24° E. 9.2'.

Corner research on file with Gogebic County records.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
At the corner position I set a 2" x 30" aluminum pipe monument with a 3 1/4" stamped aluminum cap and the following new B.T.s (all measurements taken to a nail in side of tree)

Yellow Birch	11"	N.41° W.	23.62'
Red Maple	11"	N.21° E.	25.62'
Sugar Maple	8"	S.50° E.	25.91'
Steel sign rail	6'	S.83° W.	2.43'

WORK GROUP APPROVED
Richard L. Drahn 9/21/99
COUNTY REPRESENTATIVE

Signed by Richard L. Drahn Date September 19, 1999

Surveyor's Michigan License No. 21564



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1976
REVISED JAN., 1983
REVISED OCT., 1996