

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Register's Office }
Gogebic County } ss.

Gogebic

(County)

Located in:

Corner Code #

1. Public Land Survey

T48NR 46W

D- 1

T49NR 46W

D- 13

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Quarter corner 5 & 32, T. 48-49 N., R. 46 W

I, John P. Goss, in a field survey on April 26, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by John Burt, U.S. Deputy Surveyor, on Sept. 11, 1847.

Original bearing trees: Hemlock 10" N 64° E 18 links (11.88')

Hemlock 6" N 33° W 16 links (10.56')

On May 1, 1980, Richard L. Drahn, RLS, restored corner position at record bearing and distance from the remains of the two original bearing trees.

He set a 2" iron pipe with 3" brass tablet, stamped to indicate the corner position. He established the following reference objects:

8" Hemlock - N 68° E - 33.5 ft.; 8" Hemlock - S 51° E - 23.2 ft.;

8" Hemlock - S 58° W - 45.2 ft.; 7' Metal sign post - S 24° W - 1.4 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

He recorded said corner in Liber 2, page 93 of Land Corners for Gogebic County

Found Richard L. Drahn monument and reference objects.

I updated the monument and accessories as noted below to state and county specification.

Act 74 research on file.

PEER GROUP APPROVED

Richard L. Drahn 5/11/99

COUNTY RECORDED

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From found monument I established the following existing and new reference objects:

13" Hemlock N 68° E 33.77 ft.

12" Hemlock S 51° E 23.17 ft.

12" Hemlock S 58° W 45.17 ft.

6" Maple N 28° W 8.66 ft.

7' Metal sign post S 24° W 1.4 ft. to face

(All measurement to nail in side of tree)



Signed by John P. Goss

Date April 27, 1999

Surveyor's Michigan License No. 23509