

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }
Gogebic County }

Received for record the
22ND day of OCTOBER
A. D. 1999 at 1:40 o'clock
P m., and recorded in
Liber 7 of CORNERS
on page 259
Ramona Collins, Dep.
Register of Deeds

Register of Deeds Stamp & File Number

For corners in

Gogebic

(County)

Located in:

Corner Code #

1. Public Land Survey

T48NR 46W

K-5

2. Property Controlling
in Section

S

T

R

3. Miscellaneous
Property in Sec.

S

T

R

4. Lot No. , Recorded Plat

5. Private Claims

Section corner 11, 12, 13 & 14, T48N, R46W

I, John P. Goss, in a field survey on Sept. 28, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5		4		3		2			
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt, on May 26, 1851.

Original bearing trees: Hemlock 8" S 32° W 11 links (7.26 ft.)
Hemlock 30" N 50° E 36 links (23.76 ft.)

Richard L. Drahn, 21564, on March 3, 1979, restored corner position at record bearing and distance from the remains of the two original bearing trees. He set a 2" iron pipe with 3" brass tablet, stamped to indicated the corner position. He established the following reference objects: 6" S. Maple - N120E 6.4 ft.; 12" S. Maple - S47°E - 44.0 ft.; 7" S. Maple - S 44°W - 21.35 ft.; 6' Metal sign post - S190 E - 1.7 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner.

He recorded said corner in Liber 2, page 49 of Land Corners, on 12-06-79

Found Richard L. Drahn, monument and accessories.

Found SW Hemlock original bearing tree, now stump hole.

Act 74 research on file

DEED GROUP APPROVED

Richard L. Drahn 10/14/99
COUNTY REGISTRATION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

From the found monument I established the following new and existing reference objects:

8" Sugar Maple	N 120° E	6.45 ft.
16" Sugar Maple	S 47° E	44.08 ft.
10" Sugar Maple	S 44° W	21.36 ft.
8" Sugar Maple	N 80° W	12.30 ft.
6' metal sign post	S 190° E	1.74 ft. to face
(Measurement to nail in side of tree)		



Signed by John P. Goss

Surveyor's Michigan License No.

23509

USFS J-21

Date Sept. 28, 1999