

SURVEY &  
REMONUMENTATION

OCT 03 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic

(County)

Located In:

Corner Code #

1. Public Land Survey

T 49N R 47W

G 6-7

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

M.C. between sec's. 15 and 16

I, John P. Goss, in a field survey on August 3, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by William Ives on Sept. 28, 1848. Set post

Original bearing trees: 12" Hemlock N 61° E 10 links

12" Sugar Maple S 46° W 15 links.

John Garske reset corner by projecting line from Section corner South, through GLO line tree. He recorded said corner in Liber 2 page 515 of Land Corners for Gogebic County. He established the following bearing trees and reference objects. 8" Cedar S 66° W 7.42'

8" Maple S 50° E 20.98'

To a 2" I.D. pipe with 2" brass cap, marked to indicated corner position.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I found the 2" iron pipe with brass cap and it checked with Garske witnesses.

I updated the accessories as noted below to state and county specification.

Act 74 research on file.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the 2" iron pipe with brass cap, I established the existing and new bearing trees and reference objects.

11" Cedar S 66° W 7.42'

9" Maple S 50° E 20.98'

14" Cedar N 48° E 9.51'

6' rail & sign N 08° W 1.01'

PEER GROUP APPROVED

Richard L. Dahn 8/8/96  
COUNTY REPRESENTATIVE



Register's Office  
Gogebic County

Located for record the

16<sup>th</sup> day of August

A. D. 19 96 at 10:30 o'clock

A sec. and recorded in

Liber 5 of CORNERS

on page 407

Shirley Collins, Deputy  
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Signed by John P. Goss

Date Aug 5, 1996

Surveyor's Michigan License No. 23509

Fed. No. L-M 13

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983