

SURVEY & REMONUMENTATION

MAY 16 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Register's Office Filing Requirement of Act 74, Mich. P.A. 1970 Gogebic County

For corners in

Gogebic

(County)

Located In:

Corner Code #

1. Public Land Survey

T49NR 45W A- 1
T50NR 45W A- 13
T49NR 46W M- 1
T50NR 46W M- 13

2. Property Controlling in Section

S T R
S T R
S T R
S T R

3. Miscellaneous Property in Sec.

4. Lot No. , Recorded Plat

5. Private Claims

Sec. cor. common to sec's. 31, 36, 6 & 1

I, John P. Goss, in a field survey on Oct. 16, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Austin Burt in Sept. 1847. Set Cedar post.
Original bearing trees: Hemlock 14" S 48° E 40 links
B. Ash 12" N 51° W 52 links

On July 31, 1980, Keith Sackett, RLS for DNR found a 2" I.D. iron pipe marked T.49-50 N., R.45-46 W., TWN., 31, 36, 6 & 1, 1959. He accepted said corner and recorded it in Liber 2, page 124 of Land Corners for Gogebic County. He established the following bearing trees and reference objects: 8" Ash- S 66° W- 23.7, S-1, NBT; 2" W. Birch- S 78° E- 22.6', S-6, NBT; 5" Maple- N 29° W- 29.7, S-36, NBT.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I found the 2" I.D. iron pipe with cap marked T. 49-50 N., R.45-46 W., TWN; 31, 36, 6, & 1; 1959. It checked with Keith Sackett witnesses. I updated the accessories as noted below to state and county specification.

Act 74 research on file.

PEER GROUP APPROVED
Richard L. Deane 12/11/96
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the 2" I.D. iron pipe with cap marked T.49-50 N., R.45-46 W., TWN; 31, 36, 6, & 1; 1959. I established the existing and new bearing trees and reference objects.

10" Ash S 66° W 24.34', S-1, NBT
5" W. Birch S 78° E 22.83', S-6, NBT
9" Maple N 29° W 30.00', S-36, NBT
8" Maple N 16° E 33.37'
6' Rail & Sign North 1.31'

Measurements to trees are to nail in side of tree.

Signed by John P. Goss

Date Oct 17, 1996

Surveyor's Michigan License No. 23509

Fed. No. Z-1

Received for record the
12th day of DECEMBER

A. D. 1996 at 2:30 o'clock

P M., and recorded in

Liber 6 of CORNER

on page 90

Ramona L. Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		

