

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. 25 N. 10 W.	I-13, J-13
2. PROPERTY CONTROL- ING IN SECTION_____	T. _____ N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION_____	T. _____ N. S. R. E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on OCTOBER 12, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

B. (CONTINUED)

XX  
J-13 (CONT) WE ALSO FD FARGO'S 24" W PINE STUMP (12" MAP GROWING UP OUT OF MIDDLE OF STUMP), N04°E, 75.2'.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-13 FD 1 1/2" X 36" IRON PIPE AS SET BY L.L.S., R. MITCHELL OVER FD 4" SQUARE POINTED 36" LONG CED POST, 30" BELOW RD SURFACE, & 1 1/4" X 16" WELL PIPE LAYING HORIZONTAL, 12" DEEP, 2 FT EAST, PER H.F. NORTHROP 1896 SURVEY. (H.F.N. FD OLD STK UNDER CAUSEWAY & STP OF ONE GOV'T WIT, A BALSAM & SET NEW CED STK). 1/2" REROD BY RLS D.A. ANKROM IS S54°20'W 10.65'

J-13 FD STD WEX CO MON, OLD SCRIBED 4" SQ POST (1' ABOVE GROUND), 1" FARGO PIPE ALONG SIDE MON AND STONE 1.5' EAST OF MON AS FD BY H.F. NORTHROP, CO SURVEYOR, LIBER 1, PGS 56 & 57, JULY 1896. NORTHROP HAD BOTH 1838 U.S. B.T'S (DOWN); FARGO (1913) HAD BOTH U.S. B.T'S & D.A. ANKROM (C.P.C.-1975) FD FARGO 1" PIPE & ADDED WEX CO MON.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: (CONT.)

I-13 FD 1 1/2" PIPE AT E EDGE GRAVEL RD.

CED FN POST N48°W 45.00

8" W BIRCH N14°W 104.33

4" CED STUMP N86°E 23.30

SET CED POST

W/LOC TAG. EAST 13'

4" CEDAR S34°E 44.7'

J-13 FD STD WEX CO MON & SET CED POST W/LOC TAG

9" MAPLE S10°E 26.62

11" OAK N45°W 69.79

6" TW MAPLE S50°E 19.25

18" R PINE N65°E 80.05

SIGNED BY Carl F. Roser 01-17-86 DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

PARADISE TWP  
GD. TRAVERSE CO.