

LIBER 1103 HAVE 706

MAY 07 1997

COMMISSION Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	rming Requirem	ent of Act 14, Mich. F.A. 197	•
Grand Traverse	Located In:	Corner Code #	STATE OF HICHIGAN GRAND TRAVERGE COUNTY
Public Land Survey	T <u>25N</u> R <u>11W</u> T R T R		27 DEC 96 2:29 P.M.
Property Controlling in Section	T R S T R S T R		KARON ANDERSON REGISTER OF DEEDS
3. Miscellaneous Property in Section	ST R ST R		Register of Deeds Stamp & File Number
	, Recorded Plat		A B C D E F G H I J K L
5. Private Claims			2 6 5 4 3 2 1 3
do hereby certify that under in lines 1 and 2 above were i manual of survey instructi Management or by a decree 5 above were in conforman	e, in a field survey onSeptemb requirements of P.A. 74, Michigan P.A. of in conformance with regulations and rules ons of the United States Department of a Court of Law and/or that the corne ace with the rules of the Michigan Board stablished, re-established, monumented	of 1970, the corner points mentioned is therefore as required in the current to of the Interior, Bureau of Lander points mentioned in lines 3, 4 and d of Professional Surveyors or by a	4 7 8 9 10 11 12 12 13 14 15 14 15 14 15 14 15 15 16 15 16 15 16 15 16 16 15 16 16 15 16 16 16 16 16 16 16 16 16 16 16 16 16
	corners, all in the same town and ra	nge, may be recorded	11
1/4 cors Nor "Northrop fin and a stake perpetuation his Cert. Of a rebar 5.95 Pg.191. LCR i in1974 L.1, I Mitchell find B. Description of corne C-7) Fd Verba wits a South withi 5/8" iron wit	th, South, East & West, ds Slawson stone and adds in 1909. DNR Surveyor of the Waterman Corner. De Survey, L.1, Pg.884. Don' North and a bolt spike by Jerry Wilcox RLS 13102 Pg.773. Louie Czubak finds a 5/8" iron at Verba poster evidence found and/or method a and iron in place. Verba n a ft. Also fits State	as recorded in L.1, Pg Cedar Stake and Survey Shadco finds a 1" iro lameter RLS 13030 finds Verba RLS 13603 finds a 4.24' North and 1' Wes records 1" pipe in LCR s a 5/8" iron at the Vertion in 1989. pplied in restoring or reestablish the state of the	sets it on a straight line between 125 of Co. Surveyors records. or Waterman finds Slawson's stone on in 1954 and accepts it as a an iron in 1973 and records it on 3/4" pipe and a wooden stake with t, recorded Cert. Of Survey L.2, L.1, Pg.352. Don Verba has LCR erba position in 1975. Robert F. sing corner: an's line and distances East, West ft to the South & East. Also fd Jerry Wilcox recorded L.1, PG.352.
			•
C. Description of monu	iment for corner and accessories e	stablished to perpetuate locating	g the position of the corner:
a 3 1/4" h REMONUMENTATIO COr. N26°30'E - PO N70°E - Power S11°W - East N24°W - Power	x 30" flanged bottom galvan brass Cap stamped GRANI brass Cap stamped GRANI brack of Amonument box, in p wer Pole - 79.08' Pole - 83.16' Leg of Metal Road Sign - 41 Pole - 48.39' Iron & Cap - 5.94' (Wilcox	TRAVERSE COUNTY lace of found Verba 1.43' 1.43' 1.43' 1.43'	UNANIMOUSLY ACCEPTED BY THE GRAND TRAVERSE COUNTY PEER REVIEW GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 2-24-26 ROBERT F. MITCHELL, P.S., GIAIHMAN
		E OF MICHIGA	
Signed by <u>J 104</u> Surveyor's Michigan Lice	1 */	- A Bate De	CEMBER 20, 1996 IY MICHIGAN STATE BOARD OF PROFESSIONAL BURYEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983

No. 30079