## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

Located In	Corner Code #	
T 26N R 10W	I-7	
Г R		
S T R		
S T R		
C T D		
5 I R		Register of Deeds Stamp & File Number
Recorded Plat:		
		ABCDEFGHIJKLM
		2 6 5 4 4 3 4 2
	· · · · · · · · · · · · · · · · · · ·	3
I, <u>Craig W. McVean</u> , in a field survey on <u>Nov. 3</u> , 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:		
		4 - 7 - 8 - 9 - 10 - 11 - 12
		5
		6 -18 -17 -16 -15 -14 -13 -1
		7
		8 -19 -20 -21 -22 -23 -24
		9
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.		10 30 29 28 27 26 25
		11
		12 -31 -32 -33 -34 -35 -36
		13
A. Description of original monument and accessories and/or subsequent restoration:		
1) White Pine 20" \$16°W 75 2) White Pine 16" N43°E 101 - 1911 – CSR – L. 11, p. 341 – E. P. Waterman. Fd. one US wit stp (the W. Pine 20" \$16°W 75 and mark NBT) Dug at place for old stake but found no trace of old stake. Drove new Oak stake 1928 – CSR – L. 7, p. 107 – C. O. Carver. Fd. remains of old sec. cor. Post with stp. of wit. marker NBT – W. Pine 20" \$16°W 75 L. Could not find other witness. Set squared pine stake to replace 1976 – LCRC – L. 2, p. 238 – L. M. Gerschbacher. Fd. 1" iron pipe, raised with ¾" x 18" rebar and RLS cap. 3) 8" W. Pine \$38°E 44.06' 4) 8" R. Oak N17°E 36.10'		set inside a 1 ½" O.D. pipe in a square block of
County Monument being a stamp om over ¾" CIR in 1 ½" O.D. iron nail & tag over found nail N. side nd 60d nail E. side 12" Oak (#7) nail & tag at found nail in NE side nd 60d nail in E. side 14" Oak (#4 nail & tag at found nail in W. side Post with location tag 33' South	ped 3 1/4" brass cap on 2 pipe in block of concrete 11" W. Pine (#5) e 12" W. Pine ) 18" W. Pine (#3)	2 1/3" x 30" galvanized iron
	T 26N R 10W T R  S T R  S T R  S T R  S T R  S T R  S T R  Recorded Plat:  Rec	T 26N R 10W I-7 T R S T