SURVEY & REMONUMENTATION

APR 0 7 1998

LIBER 1103 PAGE 776

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in			1						
Grand Traverse (County)	Located In:	Corner Code #			mra re	OF 1/1	MITO AN		
1. Public Land Survey	T <u>26N_R11W</u> TR TR	<u>K-2</u>		STATE OF MICHIGAN GRAND TRAVERSE COUNTY PERMITTY 12:53 P.M. KARON ANDERSON REGISTER OF DEEDS Register of Deeds Stamp & File Number					
2. Property Controlling in Section3. Miscellaneous Property in Sec.	TR STR STR STR								
4. Lot No, Recorded 5. Private Claims I, Garth Stowe	•		A 1 2 3 by state 4	B C	D E	F G	H 7		K L M
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:				-19		16	15	—14— —23—	-13-
NOTE: Not more than 2 corners on this certificate.	, all in the same town and ran	ge, may be recorded	11 12	30	32	33-	a-27	26 === 35	36
A. Description of original mon-	ument and accessories and	/or subsequent restoration:	131						
•	found cedar post set on forms. Waterman, 1907, notes in found same iron, witness of 12" iron pipe 32" below road ence found and/or method at sections 1 and 2, T26N, F7 over top of 1" x 4' 1 P 32 accepted as a careful post.	ner survey set at proportinate ron post ran line east. Certif heck. Land comer record by d surface 2.76' NE of corner applied in restoring or reestate R11W 2" deep as noted in Mitchell propetuation of the Waterma	e distance, go ficate of surve y DeLaMater o used by DeLa blishing corner t land corner in corner from	y by Da n iron f Mater, ! : record n 1907,	LaMate ound in Batzer : on cen and is	or ,1973 1973 : and Liv sterfine s monu	, found survey, asy. of Rus mente	L2 P72	Batzer, 2. Land ad a 2
C. Description of monument for K-2: 1/4 corner common to Set 2 1/2"x30" flanged botto REMONUMENTATION 6" dec	sections 1 and 2, T26N R ⁻ m galvanized pipe with a 3	1 1W	'		-				
West 77.85' N N 53° E 126.50' N N 40° W 37.92' N S 45° W 2.76'	lail found in power pole lail found in 24" Chinese E ail found in 30" Willow ail found in 6" Maple 1/2" rod found	*	GARTH D. STOWE LAND SURVEYOR NO.	* * * 40					
Corner approved by Grand T	raverse County Peer Rev	iew Group 11-05-97	RED LAND SUP	and the state of t					
			wangate and	12.	<u>- 19 -</u>	97		·	
Surveyor's Michigan License	No. 25875	•							

UNANIMOUSLY ACCEPTED BY THE GRAND TRAVERSE COUNTY PEER REVIEW GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 11705 TO THE TRAVELLE OF 1990 AT A MEETING HELD ON 11705 TO THE TRAVELLE OF 1990 AT A MEETING HELD ON 11705 TO THE TRAVELLE OF 1990 AT A MEETING HELD ON 11705 TO THE TRAVELLE OF 1990 AT A MEETING AND ROBERT F. MITCHELL, P.S., CITATHINAN

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975

REVISED JAN., 1983 REVISED OCT., 1996