

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. <u>26</u> N. <u>12</u> W.		K-1, K-3, M-1
2. PROPERTY CONTROL- ING IN SECTION_____ T. _____ N. _____ E. S. R. _____ W.		
3. MISCELLANEOUS PROPERTY IN SECTION_____ T. _____ N. _____ E. S. R. _____ W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 2/1, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

(CONT.)

XX
K-3 (CONT) AT 64'± EAST THERE ARE FN. REMAINS EAST & SOUTH.
M-1 FD. & ACCEPTED ROUND CONC. MON. FOR FOUR TWP. COR. MON. FALLS AT FN. COR. N-S-E-W-
WITH OLD BUGGY SHAFT ON SE COR OF MON, 3'± ABOVE GROUND. THIS COR IS ALSO THE SE COR
OF "WOODSIDE VALLEY'S" SUB'N.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- K-1 RE-ESTAB. CLOSING COR. BETW. SEC'S 1 & 2 ON N. TWP. LINE OF T26N,R12W AT RECORD G.L.O. DISTANCE OF 25 LINKS (16.5') WEST OF FD. STD. COR (SE SEC. 35) AND ON LINE BETW SAID FD. SE OF SEC. 35 & FD. S1/4 COR OF SEC. 35, T27N,R12W. THE CLOSING COR OF SEC'S 1 & 2 RESTORED BY THIS METHOD AGREES WITH PRIOR SURVEYS NOTED IN OLD COUNTY SURVEYOR'S RECORDS AT REG. OF DEEDS OFFICE: E.P.WATERMAN, L.2, P.458, APR 1914 AND A.G.ERICKSON, L.2,P.513, NOV. 1957.
- K-3 FD. COR. FN POST BOTTOM PER PERLA SURVEY OF NE1/4 OF SEC. 11, FILE NO. 017211.11-1.C-2.C; L-1,P.746 OF CERT. SURVEY'S. D.N.R. MON. AS NOTED IN ITEM "C" IS A 1"X36" PIPE & ALUM. DISK IN 1 1/4"X36" PIPE DRIVEN IN WET MUCK AREA. OLD FN. REMAINS, SOUTH, WEST, N15°W &

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-1	K-3	M-1
SET D.N.R. MON & CEDAR POST.	DRIVE DNR MON AT FD OLD	FD. ROUND CONC. MON.
18" BEECH (CLUSTER) SO. 40.56	CED POST BOTTOM & SET NEW	20" CHERRY N10°E 36.03
8" MAPLE N50°W 29.16	CED POST.	20" MAPLE (CLUS) S85°E 39.36
3" MAPLE S45°W 18.94	12" MAPLE S60°W 30.3	6" W.PINE S45°E 37.42
SE COR S-35 S87°59"E 16.50	6" MAPLE N66°W 31.0	
T27N R12W	14" MAPLE N48°E 56.1	

SIGNED BY Carl F. Roser 02-03-82

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____

DATE

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____

DATE

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

GREEN LAKE TWP

GD. TRAVERSE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET