MAR 1 6 1994

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in			
Grand Traverse	Located In:	Corner Code =##	STATE OF MICHIGAN GRAND TRAVERSE COUNTY RECORDED (9
Public Land Survey	T <u>27N</u> R <u>9W</u> T R T R	1-1	30 DEC 93 10:47 A.M.
	T R S T R S T H		KARON ANDERSON REGISTER OF DEEDS
3. Miscellaneous	S T R S T R		Register of Deeds Stamp & File Number
4. Lot No, Rec 5. Private Claims			A B C D E F G H J K L N
			3
do hereby certify that under require in lines 1 and 2 above were in courrent manual of survey instruct Management or by a decree of a Cabove were in conformance with the Court of Law; established, reexpressed below: NOTE: Not more than 4 corresponding to this certificate.	rements of P.A. 74, Michigan P.A. onformance with regulations and ions of the United States Depart ourt of Law and/or that the corne the rules of the Michigan Board of established, monumented, renners, all in the same town and t	of 1970, the corner points mention of rules therefore as required in the ment of the Interior, Bureau of I repoints mentioned in lines 3, 4 and Surveyors or by a Decreed nonumented, recovered, found	n the Land 7
by Hemlock 18" S22°E 35L as survey by William Slawson and of the Grand Traverse Condated May 25, 1893 and recobar," certified boundary Traverse County. "Found 2, Page 258 of the Certific recorded in Liber 3, Page the reinlinement of M-72, B. Description of corner evidence of the Certific recorded in Surveys refered to the start, 1.4' and is accepted as a carraised to the road surface.	and Cedar 8" N54°W 26L," Usives no monument type or unty Surveyors Records. orded in Liber 1, Pages 41 survey by Peter G. Perl 1" iron bar," certified sued Surveys of Grand Travere 731 of the Certified Scindicated a 1" iron bar for dence found and/or method on to Sections 2 and 3, renced in Section "A" aborded and faithful perpet ce with a 2½" x 30" fla	witnesses for this corner witnesses for this corner "Found Northeast Corner 2 & 413 of Grand Traverse a recorded in Liber 1, arvey by Louie J. Czubek ase County. "Found 1" in arveys of Grand Traverse bund. TETAN-R9W and Sections 3 applied in restoring or reest TETAN-R9W and Sections 3 ave. Upon excavation of sition. This axle shaft wation of the position onged bottom galvanized	44 and 35 of T28N-R9W; "Wood post witnessed on dated May, 1850. "Found corner," undated ar and is recorded in Liber I, Pages 26 & 27 of Section 3," a petition by George Steele se County Surveyors Records. "Found 1" iron Page 836 of the certified surveys of Grand dated March 18, 1974 and recorded in Liber con bar," certified survey by William Batzer County. In 1964, a MDOT control survey for ablishing corner: 4 and 35 of T28N-R9W; Found 1" iron bar as this corner for remonumentation, we found a t was 36" deep and buried in an old road bed of the original corner. This position was lron pipe with 3½" brass cap stamped GRAND Section "A" above is located N40°W, 1.3'.
I-1; Section Corner commo	n to Sections 2 and 3, T2 galvanized iron pipe wit	7N-R9W and Sections 34 au th 3½" brass cap stamped	ocating the position of the corner: and 35 of T28N-R9W; I GRAND TRAVERSE COUNTY REMONUMENTATION, 4" OF Mica
N 07° E 60.78' 14" Bas N 41° E 56.15' P. Pole S 13° W 56.56' 8" Ceda S 37° W 66.26' 5" Ceda	r		ROBERT F. MITCHELL PROFESSIONAL SURVEYOR No.
Corner approved by Grand T	raverse County Peer Revie	Group on 11/3/93.	28417
Signed by	F. MIC	Date _	December 29, 1993
Surveyor's Michigan License	No28417		FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 19