LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. PA 1970

STATE OF MICHIGAN

F0				GRAN	D TRAVERSE COUNTY
For Corners In: Grand Traverse	Located	in Cor	ner Code#		RECORDED
(County)	1.1.2.11100.3			30	DEC 99 4:00 P.H.
1. Public Land Survey	T 27N	R 9W R	1-4		KARON ANDERSON
Property Controlling in Section	s T	R	RVEY &	R	EGISTER OF DEEDS
3. Miscellaneous Property in Section	S T S T	REMONU	MENTATION		Stamp & File Number
4. Lot No:	Recorded Plat:	WAR	2 2 2000	<u> </u>	
5. Private Claims:		SEC	TION	A B C D E F G	3 2 1 1 -
I, Craig W. McVean, in a fierequirements of PA 74, Mic and 2 above were in confor the current manual of sun Interior, Bureau of Land Mal corner points mentioned in lof the Michigan Board of established, re-established,	chigan PA of 1970, the commance with regulations are vey instructions of the Urnagement or by a decree of the Sand Surveyors or by monumented, recovered.	rner points mention rules therefore ited States Depoi a Court of Law e in conformance a Decree of a found as expressional as expression.	oned in lines 1 as required in artment of the and/or that the with the rules Court of Law; ed below:	3 4 7 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	-10 -1112 -151413 -222324
NOTE: Not more than 2 be recorded on this cer		me town and r	ange, may	10 30 29 28	27 26 25 3
				13	
A. Description of original	monument and access	ories and/or sub	sequent restoration	on:	
-E.P. Waterman – 19 5" dia. w/ nail & spil set about 10 years old rotten stake was who helped Steven let stand – stake is #58 to #18 -C.O. Carver – 1930 Waterman distance	24 links 33 links - L. 1 P. 29 - Sec. 10 5 007 - L. 2 P. 292 - Ind. Re driven in the center of ago by Surveyor Stever is found according to 6 as. Concluded that it was 3' E & 2.6' N of straight - L. 8, P. 336 - set iron on Line.	Survey large cedar stal if top for ¼ post is. When & whiccounts of mei is correctly place line between i at Record	#2841 Ni St Re St Ni ere St n - LCRC ed & w/ cap Re Re	L. 3, P. 350-1990, R. Mitch 7 — Set per Waterman Note 67°E 8" Red Pine 91.51' 52°E 10" Red Pine 97.81' 66°W 36" Maple 64.40' 38°W 8" Red Pine 66.39' 30°W 1 ½" iron pipe 3.24' (C. 3, P. 807-1998, D. Grier, a #33978 reset per Mitchell ed Pine 12" N50°E 100.82' ed Pine 14" S75°E 87.11' ed Pine 12" N70°W 65.97'	Carver Corner) Jr., ½" x 18" rebar
B. Description of corner e			-	-	
intersection with san	id road N & E - Mitchell	& Carver Irons	removed during re	ded witnesses, in Gravel Ro ecent road construction. Ac erpetuation of the position o	cept Mitchell's
	3.24'(R) from I-4 to Can f 3' E of Line as noted b			rver position since he set of t.	n line between I-3 & I-5
C. Description of monume	ent for corner and acces	ssories establisl	hed to perpetuate	locating the position of the o	
N 45° E 50' to set E S 77° W 123.61' to N 35° W 66.41' to s N 68° E 91.38' to s S 51° E 97.72' to s S 22° E 137.94' to	capped Rebar #33978 x 30" galv. Iron pipe in Blue Carsonite Post w/ I set N & T in S side 32" set N & T in SW side 9" et N & T in N side 8" R. et N & T in SW side 14" set N & T in W side 15" o Carver position – Ref.	ring of stone oc. Tag S. Maple R. Pine (RM, D Pine scribed 'X R. Pine scribed R. Pine scribed	G) BT (RM, DG) 1'XBT (RM, DG)	emon.	CRAIG W. MCVEAN PROFESSIONAL SURVEYOR No. 39088
Signed by:	101, 1	m. II		Date de 15	112/1000
Signed by:	my 110.	100 V	en-	Dated: / ¿	113/1999
SUNAMINOVISTICACE GRAND TRAVERSE REVIEW GROUP AS CORNER UNDER MICH	COUNTY PEER	988		· · · · · · · · · · · · · · · · · · ·	

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN. 28, 1971 Revised May 14, 1975 Revised Jan. 1983 Revised Oct. 1995