STATE OF MICHIGAN GRAND TRAVERSE COUNTY

APR 2 6 1996

C-6;

C-6;

C-6;

COMMISSION	LAND CORNER RE	CORDATION CERTIFI	CATE	RECORI	JED
For corners in	Filing Requiremen	t of Act 74, Mich. P.A.	1970	27 DEC-95 3	3):35 P.M.
~ 1 ···	ted In:	Corner Code #		KARON ANI REGISTER (BERBON
т Т Т	28N R 9W R R R R R R R R R R R R R R R R R R R				
in Section S T	R R R	Deg-#/			
	R	the state of the s	Register of	Deeds Stam	p & File Number
4. Lot No, Recorded Plat 5. Private Claims				B C D E	F G H I J
			3		
I, Robert F. Mitchellin a field surved on hereby certify that under requirements of P in lines 1 and 2 above were in conformance with manual of survey instructions of the United Management or by a decree of a Court of Law 5 above were in conformance with the rules Decree of a Court of Law; established, re-estates expressed below:	.A. 74, Michigan P.A. of 19 th regulations and rules the ed States Department of v and/or that the corner p of the Michigan Board of	970, the corner points mention erefore as required in the curr f the Interior, Bureau of La oints mentioned in lines 3, 4 a f Professional Surveyors or b	ned 6 1 rent 7 and 8 1 Dy a 9 und 10 3		6 - 15 - 14 - 1 - 22 - 23 - 1 - 26 - 1
NOTE: Not more than 4 corners, all in th on this certificate.	e same town and range	e, may be recorded	11 12 13	32 3	3-34-35-
A. Description of original monument ar	nd accessories and/or	subsequent restoration:		<u> </u>	
Lewis J. Czubak & Assoc., Traverse City.	N-R9W; "Wood stake Wadsworth dated Ap 16" x 10" with "X" th Mitchell & Assoc. in L.1, Pg.196 of C Waterman dated Novox. West & Cor", an Czubak & Assoc., Tr. 974 and recorded in la Stoudt & Assoc. d	witnessed by Elm 18" N ril 1852. "Fd old pos on top and i on side" Kingsley, MI. "A stor o. Surveyor records of ember 29, 1907 and recorded location a averse City. "Set R.R. L.2, Pg.84 of LCR's of ated Dec. 11, 1978 and	41°E 12 lks and the string ground a string ground a string ground and the string ground	nd Birch 18" and both wit C.P. Tuller curvey by Co. se Co. "Fd Surveyor's r survey by Pe survey infor erse Co. "Fo	s63°W 14 lks" nesses, set pi dated Septembe Surveyor Ally stone with "X ecords of Gran ter Perla date mation", LCR h d 1" iron bar cords of Goslin
B. Description of corner evidence foun	d and/or method appl	ied in restoring or reestal	blishing corner:		
The common to Secs 17 & 18, T28N N-S blacktop road as established lis accepted as a careful and fai position with a 2½ x 30 flange Remonumentation, in a monument bo	-R9W; Fd a large gre by C.P. Tuller in 18 thful <u>perpetuation</u> d bottom galvanized x 2" below the surf	ey granite stone with " 91 at a found post with of the position of th iron pipe with a 3¼" ace of a N-S blacktop	X" on top 4.5 h both Govt, i he original co brass Cap st road.	below the bearing tree orner. Remo amped Grand	surface of the s standing and onumented this casaverse Co.
C. Description of monument for corner				PROPE PROFE SUAN	ERT F. CHELL SSIGNAL VEYOR Jo. 417
C. Description of monument for corner	and accessories esta	blished to perpetuate loca	ating the position	م المراجية on of the cont	3810NP
1 Cor common to Secs 17 & 18, T281	N-R9W;		- · ·		
A $2\frac{1}{2}$ " x 30" flanged bottom galvani a monument box 2" below the surface	zed iron pipe with a se of a N-S blacktop	ı 3‡" brass Cap stamped o road.	l Grand Traver	se Co. Remor	numentation in
S62°W - 1" Iron bar - 3.05' S81°W - P.Pole - 29.31' N44°W - 20" Maple - 142.82' N45°E - Service Pole - 115.80'			UNANIMI GRAND REVIEW CORNER	OUSLY ACCE	PTED BY THE OUNTY PEER THE OFFICIAL

Signed by_ Surveyor's Michigan License No._ 28417

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983

Date

F. MITCHELL, P.S., CITATHMAN