## SURVEY & REMONUMENTATION

LIBER 003 PAGE 587

APR 27 1995

## COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74. Mich. P.A. 1970

For corners in Grand Traverse		Located In:	Corner Code ##	STATE OF MICHIGAN GRAND TRAVERSE COUNTY	
	County			RECORDED	
1.	Public Land Survey	T R	н-9	30 DEC 94 1:35 P.M.	
2.	Property Controlling	S T R		KARON ANDERSON REGISTER OF DEEDS	
in Section         S T R				Register of Deeds Stamp & File Number	
4.	Lot No, R	ecorded Plat		A B C D E F G H I J K L N	
do in cu Ma ab Co ext NC	hereby certify that under req lines 1 and 2 above were in irrent manual of survey instru anagement or by a decree of a love were in conformance with ourt of Law; established, re pressed below:  OTE: Not more than 4 co on this certificate.  Description of original re-	in a field survey on Octobulrements of P.A. 74, Michigan P.A. of conformance with regulations and actions of the United States Departs a Court of Law and/or that the corner in the rules of the Michigan Board of e-established, monumented, re-morners, all in the same town and monument and accessories and G.L.O. notes and with the same town and the content of the court of the monument and accessories and with the content of the court	of 1970, the corner points mention of rules therefore as required in the ment of the Interior, Bureau of Lair points mentioned in lines 3, 4 and Land Surveyors or by a Decree of conumented, recovered, found of range, may be recorded.	ed 6 18 17 16 15 14 13 16 15 16 15 16 16 16 17 16 16 16 16 17 17 16 17 18 18 18 18 18 18 18 18 18 18 18 18 18	
I	<b>3</b>	rveyor records of		er 3, Pg. 18 and	

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

of 1916 filed in Liber 10, Pg. 25.

H-9: No physical evidence of original G.L.O. witnesses were found. Found 5/8" x 18" re-rod with cap (illegible) next to plow point and replaced with Grand Traverse County monument.

This common is accepted as a careful and faithful perpetuation of the position of the original corner.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- H-9: 1/4 Corner common to Sections 22 & 27, T.29N., R.10W.
  Perpetuated with 2-1/2" x 30" flanged bottom galvanized iron
  pipe with 3-1/4" brass cap stamped GRAND TRAVERSE COUNTY
  REMONUMENTATION.

S60°E 6.03'

Surveyor's Michigan License No.

10" Red Pine

North 28.46' Triple Maple

S62°W 17.58' 8" Ash

S02°E 29.05' 8" Red Pine

Corner approved by the Grand Traverse County Peer Review on 12-29-94.

Signed by \_\_\_\_\_\_ Date \_\_\_\_\_

GARTH
D. STOWE
LAND
SURVEYOR
NO.
25875

W MICHIGAN STATE

W MICHIG