## SURVEY & REMONUMENTATION

FEB 2 6 1998

Surveyor's Michigan License No. 35991

SECTION	LAND CO Filing R	ORNER RECORDATION Clequirement of Act 74, Mic	ERTIFICATE n. P.A. 1970	· •
For corners in			1	12/30/97
	Located In:	Corner Code #	arbara K	es of Deeds 2:13 PM
Leelanau (County)			L#elanau R	OTV PARI VIVA
	T 29NR 11W	I-4 (Bingham Twp.)	04B00002 F	
1. Public Land Survey	T_R	-	0,000,000	
	TR			
	TR			#51 <b>1</b>
2. Property Controlling	s TR			
in Section	S TR			a File Mumbar
3. Miscellaneous	S T_R		F	Register of Deeds Stamp & File Number
Property in Sec.	<u> </u>			:
		•		B C D E F G H I J K L !
4. Lot No, Record	led Plat		- 1 A	
5. Private Claims			2	
			3	10.
	in a field survey on N	lovember 27, , 19 97 do her per points mentioned in lines 1 and	eby state that 4	-7-18-1-10-1
" 1 A 74 Mi	chinan P A Of 1510, the con	tiot political in a must of current if	nstructions of 💛 🐪	
				-18-17-16-15-13-13
the United States Department of the	ne interior, Bureau or Carland aned in lines 3, 4 and 5 at	Nanagement of by a decree tife a coopove were in conformance with the of Law; established, re-established,	monumented,	
Attaches Roard Of Fally Surveyor	C Q)	ove were in conformative with the of Law; established, re-established,	8	19 20 21 -22 -23 -24
recovered found as expressed to	,,,,,,,		9	
NOTE: Not more than 2 corr	ners, all in the same town	and range, may be recolded	10	30 29 28 27 26 25
on this certificate.			11	
		والمعاددة	n: 12	31 32 33 34 35 36 36 36 36 36 36 36 36 36 36 36 36 36
A Cheerintian of original ma	onument and accessorie	s and/or subsequent restoratio	II. 1*	
				- TOOMED & AND CORNER
1-4; West 1/4 corner of S	ection 11			APPROVED LAND CORNER
1-4; West 1/4 corner of S	ection 11			25 A 345 OF 1990
I-4; West 1/4 corner of S G.L.O. notes: set	ection 11 1/4 post at 40.00 chains			P.A. 345 OF 1990 LEELANAU COUNTY
I-4; West 1/4 corner of S G.L.O. notes: set	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks.			P.A. 345 OF 1990 LEELANAU COUNTY
I-4; West 1/4 corner of S G.L.O. notes: set	ection 11 1/4 post at 40.00 chains			P.A. 345 OF 1990 LEELANAU COUNTY
I-4; West 1/4 corner of S G.L.O. notes: set Cer He	ection 11 1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.		•	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. 1140 Mar.
I-4; West 1/4 corner of S G.L.O. notes: set Cer He	ection 11 1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.		•	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. 1140 Mar.
I-4: West 1/4 corner of S G.L.O. notes: set Cer He: B. Description of corner e	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks. widence found and/or ma		•	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. 1140 Mar.
I-4: West 1/4 corner of S G.L.O. notes: set Cer He: B. Description of corner e	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks. widence found and/or ma	ethod applied in restoring or rea	establishing corner.	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. MMLOTAL
I.4: West 1/4 corner of S G.L.O. notes: set Cer He:  B. Description of corner e I-4: West 1/4 corner o	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks. evidence found and/or ma	ethod applied in restoring or rea	establishing corner.	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 1/-24-97  COUNTY REP. Myllona  1990 Livasy reset cor. with rerod from witnesses
I.4: West 1/4 corner of S G.L.O. notes: set Cer He:  B. Description of corner e I-4: West 1/4 corner o County Survey Rec	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks. evidence found and/or materials f Section 11 ords - well point	ethod applied in restoring or rea 1987 Mitchell - well point found - file	establishing corner.	P. A. 345 OF 1990 LEELANAU COUNTY  DATE: //-24-97  COUNTY REP. /////////////////  1990 Livasy reset cor. with rerod from witnesses  28" manie \$63°E 14.15"
I.4: West 1/4 corner of S G.L.O. notes: set Cer He:  B. Description of corner e I-4: West 1/4 corner o County Survey Rec	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks. widence found and/or materials f Section 11  ords - well point E 2.8	ethod applied in restoring or rec 1987 Mitchell - well point found - file 20" maple S61°E 14.10' 10" birch S33°W 4.35'	establishing corner.	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 1/-24-97  COUNTY REP. Myllona  1990 Livasy reset cor. with rerod from witnesses
I-4: West 1/4 corner of S G.L.O. notes: set Cer He:  B. Description of corner e I-4: West 1/4 corner of County Survey Rec 9" cedar N41°48" 8" Blash S05°44"	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  widence found and/or material fraction 11  ords - well point  E 2.8' E 6.3'	ethod applied in restoring or rec 1987 Mitchell - well point found - file 20" maple S61°E 14.10"	establishing corner.	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: //-24-97  COUNTY REP. //////////////////////  1990 Livasy reset cor. with rerod from witnesses  28" maple \$63°E 14.15' 6" basswod N08°W 21.56'
I.4: West 1/4 corner of S G.L.O. notes: set Cer He:  B. Description of corner e I-4: West 1/4 corner o County Survey Rec	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  widence found and/or material fraction 11  ords - well point  E 2.8' E 6.3'	ethod applied in restoring or rea 1987 Mitchell - well point found - file 20" maple S61°E 14.10' 10" birch S33°W 4.35	establishing corner.	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: //-24-97  COUNTY REP. //////////////////////  1990 Livasy reset cor. with rerod from witnesses  28" maple \$63°E 14.15' 6" basswod N08°W 21.56'
I-4: West 1/4 corner of S G.L.O. notes: set  Cer. Hei  B. Description of corner e I-4: West 1/4 corner of County Survey Rec 9" cedar N41°48" 6" B. ash S05°44' 6" cedar N74°28"	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  evidence found and/or material from 11  ords - well point  E 2.8' E 6.3' W 11.7'	ethod applied in restoring or rea 1987 Mitchell - well point found - file 20" maple S61°E 14.10' 10" birch S33°W 4.35' 12" birch N49°W 3327'	establishing corner: ed L.C.R.C #251	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. 11-24-97  1990 Livasy reset cor. with rerod from witnesses  28" maple \$63°E 14.15' 6" basswod N08°W 21.56' 8" cedar N63°W 5.14'
I-4: West 1/4 corner of S G.L.O. notes: set  Cer. Hei  B. Description of corner e I-4: West 1/4 corner of County Survey Rec 9" cedar N41°48" 6" B. ash S05°44' 6" cedar N74°28"	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  evidence found and/or material from 11  ords - well point  E 2.8' E 6.3' W 11.7'	ethod applied in restoring or red 1987 Mitchell - well point found - file 20" maple S61°E 14.10' 10" birch S33°W 4.35' 12" birch N49°W 3327'	establishing corner: ed L.C.R.C #251	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. 11-24-97  1990 Livasy reset cor. with rerod from witnesses  28" maple \$63°E 14.15' 6" basswod N08°W 21.56' 8" cedar N63°W 5.14'
I.4: West 1/4 corner of S G.L.O. notes: set  Cer He:  B. Description of corner e I-4: West 1/4 corner o  County Survey Rec 9" cedar N41°48" 6" B. ash S05°44" 6" cedar N74°26"  C. Description of monument	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  evidence found and/or material from the section 11  ords - well point  E 2.8' E 6.3' W 11.7'	ethod applied in restoring or reconstruction of the second applied in restoring or reconstruction of the second applied in restoring applied in restoring or reconstruction applied in restoring applied in restorin	establishing corner. ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. Multiplication  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15' 6" basswod N08°W 21.56' 8" cedar N63°W 5.14'  mer:
B. Description of corner of S  G.L.O. notes: set  Cer He:  B. Description of corner of  1-4: West 1/4 corner of  County Survey Rec  9" cedar N41°48" 6" B. ash S05°44' 6" cedar N74°28"  C. Description of monument	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  widence found and/or material from the section 11  ords - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11	ethod applied in restoring or realise.  1987 Mitchell - well point found - file.  20" maple S61°E 14.10'  10" birch S33°W 4.35'  12" birch N49°W 3327'  established to perpetuate locating to	establishing corner: ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. MALLO MALLO  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15" 6" basswod N08°W 21.56" 8" cedar N63°W 5.14"
B. Description of corner of S  G.L.O. notes: set  Cer He:  B. Description of corner of  1-4: West 1/4 corner of  County Survey Rec  9" cedar N41°48" 6" B. ash S05°44' 6" cedar N74°28"  C. Description of monument	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  widence found and/or material from the section 11  ords - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11	ethod applied in restoring or realise.  1987 Mitchell - well point found - file.  20" maple S61°E 14.10'  10" birch S33°W 4.35'  12" birch N49°W 3327'  established to perpetuate locating to	establishing corner: ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. MALLO MALLO  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15" 6" basswod N08°W 21.56" 8" cedar N63°W 5.14"
B. Description of corner of S  G.L.O. notes: set  Cer He:  B. Description of corner of  1-4: West 1/4 corner of  County Survey Rec  9" cedar N41°48" 6" B. ash S05°44' 6" cedar N74°28"  C. Description of monument	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  widence found and/or material from the section 11  ords - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11	ethod applied in restoring or realise.  1987 Mitchell - well point found - file.  20" maple S61°E 14.10'  10" birch S33°W 4.35'  12" birch N49°W 3327'  established to perpetuate locating to	establishing corner: ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: //-24-97  COUNTY REP. MML O'ALL  1990 Livasy reset cor. with rerod from witnesses 28" maple \$63°E 14.15' 6" basswod N08°W 21.56' 8" cedar N63°W 5.14'  ner: osition of the original corner by the Leelanau 14" galvanized iron pipe 3' long with a brass cap.
B. Description of corner of S  G.L.O. notes: set  Cer He:  B. Description of corner of  1-4: West 1/4 corner of  County Survey Rec  9" cedar N41°48" 6" B. ash S05°44' 6" cedar N74°28"  C. Description of monument	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  widence found and/or material from the section 11  ords - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11	ethod applied in restoring or realism.  1987 Mitchell - well point found - file 20" maple S61°E 14.10' 10" birch S33°W 4.35' 12" birch N49°W 3327'  established to perpetuate locating to the same as a careful and faithful reest bup on November 24, 1997 and	establishing corner: ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97 COUNTY REP. NUMBER  1990 Livasy reset cor. with rerod from witnesses 28" maple S63°E 14.15' 6" basswod N08°W 21.56' 8" cedar N63°W 5.14'  ner: osition of the original corner by the Leelanau 14" galvanized iron pipe 3' long with a brass cap.
B. Description of corner et l-4: West 1/4 corner of County Survey Rec 9" cedar N41°48" 6" B. ash S05°44' 6" cedar N74°28"  C. Description of monument l-4: West 1/4 corner of Iron bar and cap #3 County Remonument	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  widence found and/or material state of Section 11  ards - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11  31611(Livasy) is accepte entation Peer Review Groes:	ethod applied in restoring or recommendation of the second applied in restoring or recommendation of the second applied in restoring the second and faithful reestory on November 24, 1997 and New Witness:	establishing corner: ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97 COUNTY REP. NUMBER  1990 Livasy reset cor. with rerod from witnesses 28" maple S63°E 14.15' 6" basswod N08°W 21.56' 8" cedar N63°W 5.14'  ner: osition of the original corner by the Leelanau 14" galvanized iron pipe 3' long with a brass cap.
I.4; West 1/4 corner of S G.L.O. notes: set  Cer He:  B. Description of corner e I-4; West 1/4 corner o County Survey Rec 9" cedar N41°48" 6" B. ash S05°44" 6" cedar N74°26"  C. Description of monument I-4; West 1/4 corner o Iron bar and cap #3 County Remonume Existing Witnesse 28" maple Si	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  Midence found and/or may section 11  ords - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11  31611(Livasy) is accepte entation Peer Review Groes: 61°E 14.18'	ethod applied in restoring or recommendation of the second applied in restoring or recommendation of the second applied in restoring the second and faithful reestory on November 24, 1997 and New Witness:  6" elm \$16°E 16.53'  2" cedar N66°E 22.31'	establishing corner: ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY  DATE: 11-24-97  COUNTY REP. MALLO MALLO  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15" 6" basswod N08°W 21.56" 8" cedar N63°W 5.14"
I.4: West 1/4 corner of S G.L.O. notes: set  Cer He:  B. Description of corner e I-4: West 1/4 corner o County Survey Rec 9" cedar N41°48" 6" B. ash S05°44' 6" cedar N74°28"  C. Description of monument I-4: West 1/4 corner o Iron bar and cap #3 County Remonument Existing Witnesse 28" maple Si	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  widence found and/or material state of Section 11  ards - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11  31611(Livasy) is accepte entation Peer Review Groes:	ethod applied in restoring or recommendation of the second applied in restoring or recommendation of the second applied in restoring the second and faithful reestory on November 24, 1997 and New Witness:	establishing corner: ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY DATE: 11-24-97 COUNTY REP. 11-24-97  1990 Livasy reset cor. with rerod from witnesses 28" maple \$63°E 14.15" 6" basswod N08°W 21.56" 8" cedar N63°W 5.14"  ner: cosition of the original corner by the Leelanau 14" galvanized iron pipe 3" long with a brass cap.  STEVEN P. BYE
I.4; West 1/4 corner of S G.L.O. notes: set  Cer He:  B. Description of corner e I-4; West 1/4 corner o County Survey Rec 9" cedar N41°48" 6" B. ash S05°44" 6" cedar N74°26"  C. Description of monument I-4; West 1/4 corner o Iron bar and cap #3 County Remonume Existing Witnesse 28" maple Si	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  Midence found and/or may section 11  ords - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11  31611(Livasy) is accepte entation Peer Review Groes: 61°E 14.18'	ethod applied in restoring or recommendation of the second applied in restoring or recommendation of the second applied in restoring the second and faithful reestory on November 24, 1997 and New Witness:  6" elm \$16°E 16.53'  2" cedar N66°E 22.31'	establishing corner: ed L.C.R.C #251 he position of the corr	LEELANAU COUNTY  DATE: //-24-97  COUNTY REP. //// STEVEN P.  BYE LAND SURVEYOR  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15"  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15"  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15"  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15"  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15"  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15"  1990 Livasy reset cor. with rerod from witnesses  28" maple S63°E 14.15"  1990 Livasy reset cor. with rerod from witnesses  29
I.4; West 1/4 corner of S G.L.O. notes: set  Cer He:  B. Description of corner e I-4; West 1/4 corner o County Survey Rec 9" cedar N41°48" 6" B. ash S05°44" 6" cedar N74°26"  C. Description of monument I-4; West 1/4 corner o Iron bar and cap #3 County Remonume Existing Witnesse 28" maple 8" cedar N	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  Midence found and/or mark f Section 11  ords - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11  31611(Livasy) is accepte entation Peer Review Groes: 61°E 14.18' 63°W 5.14'	ethod applied in restoring or recommendation of the second applied in restoring or recommendation of the second applied in restoring the second and faithful reestory on November 24, 1997 and New Witness:  6" elm \$16°E 16.53'  2" cedar N66°E 22.31'	establishing corner: ed L.C.R.C #251 he position of the corr	P.A. 345 OF 1990 LEELANAU COUNTY DATE: //-24-97 COUNTY REP. //////////////////// 1990 Livasy reset cor. with rerod from witnesses 28" maple \$63°E 14.15' 6" basswod N08°W 21.56' 8" cedar N63°W 5.14'  her: cosition of the original corner by the Leelanau /4" galvanized iron pipe 3' long with a brass cap.  STEVEN P BYE LAND
I.4; West 1/4 corner of S G.L.O. notes: set  Cer He:  B. Description of corner e I-4; West 1/4 corner o County Survey Rec 9" cedar N41°48" 6" B. ash S05°44" 6" cedar N74°26"  C. Description of monument I-4; West 1/4 corner o Iron bar and cap #3 County Remonume Existing Witnesse 28" maple 8" cedar N	ection 11  1/4 post at 40.00 chains dar 12 N47W 32 lks. mlock East 23 lks.  Midence found and/or may section 11  ords - well point  E 2.8' E 6.3' W 11.7'  for corner and accessories of Section 11  31611(Livasy) is accepte entation Peer Review Groes: 61°E 14.18'	ethod applied in restoring or recommendation of the second applied in restoring or recommendation of the second applied in restoring the second and faithful reestory on November 24, 1997 and New Witness:  6" elm \$16°E 16.53'  2" cedar N66°E 22.31'	establishing corner: ed L.C.R.C #251  the position of the corresponding to the position of the policy ablishment of the policy with a 3/2	P.A. 345 OF 1990 LEELANAU COUNTY DATE: 11-24-97 COUNTY REP. 11-24-97 COU