

LAND CORNER

197

4/15/95  
R.W. Drahm

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Houghton (County) Located In: Corner Code #/

1. Public Land Survey	T	R	
	T	R	
	T	R	
	T	R	
2. Property Controlling in Section	S 31	T 47N	R 36W
	S	T	R
3. Miscellaneous Property in Sec.	S	T	R
	S	T	R

REGISTER'S OFFICE  
Houghton County, Mich.  
Received for record the 23 day of April A.D., 1995, at 11 o'clock, P.M. and recorded in Vol. 3 of Land Corner, Page 197  
D. Drahm, Registrar  
Register of Deeds Stamp & File Number

4. Lot No. Recorded Plat  
5. Private Claims  
NE 1/16 Corner, Section 31; R.47N., R.36W.

I, Richard L. Drahm, in a field survey on May 16, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:  
Corner position not set by original survey.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
Corner established at the intersection of straight lines between opposing 1/16 corner positions on the perimeter of the northeast quarter of Section 31; T.47N., R.36W.

SURVEY &  
REMONUMENTATION

MAY 16 1997

COMMISSION



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
At the corner position I set a 2 1/2" diameter by 30" long aluminum monument with a 3 1/4" aluminum cap with magnet stamped to read: T.47N., R.36W.; NE 1/16; S-31; 1994; R.L.S. 21564 from which I established the following new blazed and scribed bearing trees and/or objects:

8"	Balsam	N.21W.	11.77 feet
6"	Spruce	N.76E.	6.87 feet
10"	Red Pine	S.12W.	13.88 feet
6'	Steel Rail	S.49W.	1.0 feet

Signed by Richard L. Drahm Date February 7, 1995  
Surveyor's Michigan License No. 21564

USFS #W-4