

Houghton

Corner Code 77

Houghton County, Mich.

of April..... A. D., 1985, at 8:00
of clock..... P. M. and recorded in Vol. 3.....
of Land, Warner..... Page 193.....
..... Barney F. Wells..... Register

Register of Deeds Stamp & File Number

T R

S 31 T 47N R 36W

S **T** **R**

5 Private Claims

N 1/16 Corner, Sections 31 & 32; T.47N, R.36W.

1. Richard L. Drahn, in a field survey on May 16, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner position not set by original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner established on line between and equal distance from the east quarter corner and the northeast section corner of Section 31; T.47N., R.36W.

CLIFFEY & REINVENTATION

MAY 16 1997

COMMISSION

C Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position and 6" below the surface of a road I set a 2" x 12" concrete filled galvanized iron pipe with a 3" brass cap stamped to read: T.47N., R.36W.; N 1/16; S-31, S-32; 1994; R.L.S. 21564; from which I established the following: A 30" aluminum pipe reference monument with an aluminum cap stamped to indicate the corner position; and;

8"	Balsam	N.52W.	19.43 feet
8"	Sugar Maple	N.83E.	17.80 feet
10"	Sugar Maple	S.72E.	18.61 feet
6'	Steel Rail	N.87W.	13.10 feet

Signed by

Date March 9, 1995

Surveyor's Michigan License No. 21564

USFS #W-5

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 20, 1971
REVISED MAY 14, 1975
REVISED JAN. 1981