

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S 19 T 51N R 35W S 19 T 51N R 35W S _____ T _____ R _____	9 B8
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

I, Stephan J. Szyszkoski, in a field survey on 9 05/02/2011
B8 05/03/2011 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 19) East 1/16 corner, Section 19. Not established in the original survey.

(B8) Center of Section 19. Not established in the original survey. Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 19) Established the corner midway and on a straight line between Center of Section 1295.11'
West and Quarter corner 1295.11' East. From the corner position, an old east-west fence is 34'
North.

(B8) Established the corner at the intersection of straight lines connecting opposite 1/4 corners.
From the corner position a fence corner with old fences running south and east is 17' North and 22'
West.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9) Set 1"IDx32" I.pipe with plastic cap
stamped "MICH DNR PS 33986".
Set measuring nail with MDNR tag in the side of:
6" Ironwood N34E 9.95' mrkd "1/16S BT"
9" Sugar S52E 10.45' do
7" Sugar S03E 18.95' do
3" Ironwood N53W 2.3' do
Set sq'd cedar post/location poster adjacent.
Bearings are magnetic.

(B8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
9" Maple in clump S65E 12.95' mrkd "C1/4 BT"
4" Cherry S37W 26.05' do
10" twin Maple S77W 27.2' do
4" Balsam N06E 13.4' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 06/02/2011

For the Michigan Department of Natural Resources, Office of Land and Facilities

